

\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*

Date of preparation: 10-1-09

3011000-10H

**SECTION I PRODUCT IDENTIFICATION AND USE**

Manufacturer : **W. R. MEADOWS®, INC.**  
 Address : 300 Industrial Drive  
 : Hampshire, Illinois 60140  
 Telephone # : (847) 683-4500  
 Emergency # : 1-800-424-9300 Chemtrec

**- H M I S -**

<b> Health</b>	: 1
<b> Fire</b>	: 1
<b> Reactivity</b>	: 0
<b> Person Protection</b>	:

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,\*=Chronic)

Product Class : DIVISION 3  
 Mfg. Code I.D. : 3011000-10H  
 Trade Name : **1100-CLEAR WITH RED FUGITIVE DYE WATER-BASED CLEAR CURING COMPOUND**

**SECTION II-A HAZARDOUS COMPONENTS**

No. Component	CAS#	% By Weight	SARA 313	VAPOR PRESSURE (MM Hg @ 20 C)	LEL
1. Mineral Spirits	64732-47-8	5 – 10	NO	2.6	0.75

None of the components of this product are recognized as carcinogenic. Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

N/A: Not Applicable

**SECTION II-B OCCUPATIONAL EXPOSURE LIMITS**

No.	OSHA				ACGIH			
	PEL/TWA	PEL/CEILING	PEL/STEL	SKIN	TLV/TWA	TLV/CEILING	TLV/STEL	SKIN
1.	100 PPM	500 PPM	N/E	N/E	100 PPM	N/E	200 PPM	N/E

N/E: Not Established

**SECTION III PHYSICAL DATA**

<b>Boiling Point</b>	: 212 Degrees F.	<b>% Volatile by volume</b>	: 85.00 (Theoretical)
<b>Evaporation Rate</b>	: < 1 (ether = 1)	<b>% Volatile by weight</b>	: 84.00 (Theoretical)
<b>Vapor Density</b>	: > 1 (air = 1)	<b>Weight per gallon</b>	: 8.33 (Theoretical)
<b>PH Level</b>	: 8.80		

**SECTION IV HEALTH INFORMATION**

**EYE CONTACT:** Based on the presence of component 1 this product is presumed to be moderately irritating to the eyes. Product vapors and/or mists may also be irritating to the eyes.

**SKIN CONTACT:** Exposure may cause mild to moderate irritation. Prolonged or repeated contact may result in defatting and drying of the skin which may result in dermatitis. No irritation is likely after brief contact, but may occur after prolonged contact.

**INHALATION:** Exposure may irritate the nose, throat, respiratory tract, and other mucous membranes. Exposure to excessive vapor concentrations may cause signs of transient central nervous system depression. (e.g. headache, drowsiness, loss of coordination, and fatigue). Reports have associated repeated and prolonged occupational concentrating and inhaling the contents may be harmful or fatal.

**INGESTION:** Based on the presence of component 1 this product is presumed to be slightly toxic. Small amounts of the liquid aspirated into the lungs during ingestion or from vomiting may result in severe lung damage. While this depression. (e.g. headache, fatigue, drowsiness, dizziness, and loss of coordination).

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation may include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea. Transient central nervous system depression may be evidenced by headache, dizziness, nausea, and symptoms of intoxication; in extreme cases, unconsciousness and death may occur. Symptoms of chronic overexposure include loss of memory, loss of intellectual ability, and loss of coordination.

**AGGRAVATED MEDICAL CONDITION:** Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

**OTHER HEALTH EFFECTS:** None recognized.

Date of Preparation: 10/1/09

\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*

Date of preparation: 10/1/09

---

---

**SECTION V EMERGENCY AND FIRST AID PROCEDURES**

---

**EYE CONTACT:** Immediately flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Remove contaminated shoes and clothing. Wipe excess from skin and flush with water using soap if available. Seek medical attention if irritation occurs. Do not reuse clothing until thoroughly decontaminated.

**INHALATION:** Remove victim to fresh air and treat symptomatically. Provide oxygen if breathing is difficult. Give artificial respiration if the victim is not breathing. Seek prompt medical attention.

**INGESTION:** Do not induce vomiting. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent aspiration into the lungs. Since aspiration into the lungs can cause very serious, permanent damage, the decision of whether to induce vomiting or not should be made by a physician, hospital, or poison control center and/or transport to an emergency facility immediately.

---

---

---

**SECTION VI FIRE AND EXPLOSION HAZARDS**

---

**FLAMMABILITY CLASSIFICATION – NFPA:** Combustible Liquid – Class IIIA

- DOT: Not regulated

**FLASH POINT:** Greater than 210 degrees F. (Estimate)

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical, or carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:** Clear area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH approved self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

---

---

---

**SECTION VII REACTIVITY**

---

**STABILITY:** Stable

**HAZARDOUS POLYMERIZATION:** Will not occur

**CONDITIONS AND MATERIALS TO AVOID:** Avoid oxidizing materials

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion may yield carbon dioxide, carbon monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

---

---

---

**SECTION VIII EMPLOYEE PROTECTION**

---

**RESPIRATORY PROTECTION:** Use ventilation as required to control vapor concentrations – at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

**PROTECTIVE CLOTHING:** Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

**ADDITIONAL PROTECTIVE MEASURES:** Eye wash fountains and safety showers should be available for use in an emergency.

---

---

---

**SECTION IX ENVIRONMENTAL PROTECTION**

---

**SPILL OR LEAK PROCEDURES:** LARGE SPILLS>> Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. SMALL SPILLS>> Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

**WASTE DISPOSAL:** Observe all Federal, State and local regulations regarding proper disposal.

---

---

---

**SECTION X ADDITIONAL PRECAUTIONS**

---

Containers, even if empty, may hold product residues. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Keep containers closed/sealed when not in use.

---

=====  
The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.