

*** MATERIAL SAFETY DATA SHEET ***

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to implement the "Workplace Hazardous Materials Information System (WHMIS)". Also make this information available to any employee who requests it.

Date of preparation: 07/11/2007

3300-238

SECTION I PRODUCT IDENTIFICATION AND USE

Manufacturer : W. R. MEADOWS OF CANADA

- H M I S -

Address : 70 Hannant Court
: Milton, Canada L9T 5C1

|Health : 2 |
|Fire : 3 |
|Reactivity : 0 |
|Personal Protection : |

Telephone # : (905) 878-4122

Emergency # : 1-800-424-9300 Chemtrec

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)

Product Class : Class B, Division 2, Flammable Liquids, Class D, Division 2, Subdivision B, Toxic Materials

Product Identification Number: 3300-238

Product Identifier : SEAL-CURE 25

Product Use : Concrete Curing and Sealing Compound

SECTION II HAZARDOUS INGREDIENTS

No.	Component	CAS#	% by		ACGIH				
			Weight	LD50	LC50	TLV/TWA	TLV/CEILING	TLV/STEL	SKIN
1.	Xylene	330-20-7	65-70	4300 mg/kg*	5000 ppm/4H*	100 PPM	N/E	150 PPM	N/E
2.	Ethyl Benzene	100-41-4	5-10	3500 mg/Kg+	N/E	100 ppm	N/E	125 ppm	No
3.	Ethylene Glycol Monobutyl Ether Acetate	112-07-2	1-5	2400 mg/kg+	N/E	N/E	N/E	N/E	N/E

*A complete disclosure will be provided to a physician or nurse in the event of a medical emergency. None of the components of this product are recognized as carcinogenic.

Component data is defined in accordance with Sub-paragraph 13 (a) (i) to (iv) of the Hazardous Product Act.

SECTION III PHYSICAL DATA

Physical State	:Liquid	Vapor Density	: >1 (air 1)
Specific Gravity	:0.94 @ 15 degrees C.	Evaporation Rate	: <1 (ether1)
Odour/Appearance	:Amber liquid, Solvent odour	Percent Volatile	: 75 (by volume)
Vapour Pressure	:Not estimated	Freezing Point	: Not established
pH	:Not applicable	Boiling Point	: 137 degrees C.
Odour Threshold	:Not applicable		

Coefficient of water/oil distribution: Not available

SECTION IV FIRE AND EXPLOSION DATA

Conditions of Flammability: Ignition sources

Autoignition temp.: Not established

Means of extinction: Water fog, foam, dry chemical, or Carbon Dioxide.

Sensitivity to mechanical Impact: No

Flash point and method: 26 degrees C., Tag Closed Cup – For Xylene

Sensitivity to static discharge: No

Flammability limits: LEL: 1.1 UEL: 6.6

Hazardous combustion products: Carbon Monoxide, Carbon Dioxide and incomplete combustion products.

SECTION V REACTIVITY DATA

Chemical stability: Stable

If no, under which conditions

Incompatibility (materials to avoid): Avoid oxidizing materials

Conditions of reactivity: None

Hazardous decomposition products: None

Date of preparation: 07/11/2007

3300-238

