




SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product:	LIQUI-HARD® ULTRA	Part Number: 3360-378
Manufacturer:	W. R. Meadows® of Canada	Address: 70 Hannant Court Milton, Ontario Canada L9T 5C1
Telephone:	(905) 878-4122	In case of emergency, dial (800) 424-9300 (CHEMTREC)
Revision Date:	8/21/2015	
Product Use:	Concrete Hardener/Densifier	

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS	HAZARD STATEMENTS
Health 1	WARNING!
Flammability 0	Causes skin irritation.
Reactivity 0	Causes serious eye irritation.
Personal Protection	May cause respiratory irritation. Suspect of damaging fertility or unborn child.
	PRECAUTIONARY STATEMENTS
	Avoid direct contact.
	Avoid breathing mists/sprays.



SECTION 3: HAZARDS COMPONENTS

Chemical Name:	CAS Number	% by Weight	SARA 313	Vapor Pressure (mm Hg@20°C)	LEL (@25°C)
1. Lithium Silicate	12627-14-4	10-15	No	N/A	N/A

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313." *N/A: Not Applicable*

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Immediately flush eyes with water for fifteen (15) minutes. Seek prompt medical attention.

SKIN CONTACT: Wash affected areas with mild soap and water. Remove contaminated shoes/clothing. Seek prompt medical attention.

INHALATION: Not expected to be an exposure route as supplied. If respiratory symptoms develop, seek medical attention.

INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section II for Symptoms/Effects.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: Product will not flash due to water content.

EXTINGUISHING MEDIA: Water fog, foam, dry chemical.

CHEMICAL/COMBUSTION HAZARDS: None recognized.

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Use appropriate personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Avoid direct contact. Dike and contain spilled material. Remove source of spill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact.

SAFE STORAGE: Prevent product from freezing.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name:	OSHA				ACGIH			
	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Lithium Silicate	N/E	N/E	N/E	No	N/E	N/E	N/E	N/E

N/E: Not Established

ENGINEERING CONTROLS: None required under normal use conditions.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 100 degrees C	VAPOR DENSITY: N/A	% VOLATILE BY VOLUME: N/E
EVAPORATION RATE: <1 (Ether=1)	pH LEVEL: 11.00	% VOLATILE BY WEIGHT: 89 (Approximate)
WEIGHT PER GALLON: 8.9	PRODUCT APPEARANCE: Clear Liquid	VOC CONTENT: 0 g/L
ODOR: None	ODOR THRESHOLD: N/D	MELTING/FREEZING POINT: N/D

SAFETY DATA SHEET

Date of Preparation: 8/21/15	Page 2 of 2	3310000
<i>Section 9 continued</i>		
FLASH POINT: See Section 5	FLAMMABILITY: N/D	UEL/LEL: N/D
VAPOR PRESSURE: N/D	RELATIVE DENSITY: N/D	SOLUBILITY: N/D
PARTITION COEFFICIENT: N/D	AUTOIGNITION TEMPERATURE: N/D	DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D	<i>N/D: Not Determined</i>	
SECTION 10: STABILITY/REACTIVITY		
STABILITY: Stable.	HAZARDOUS POLYMERIZATION: Will not occur.	
CONDITIONS AND MATERIALS TO AVOID: Strong acids.		
HAZARDOUS DECOMPOSITION PRODUCTS: None recognized.		
SECTION 11: TOXICOLOGICAL INFORMATION		
EYE CONTACT: Direct contact may cause moderate to severe irritation. This product may cause corneal injury resulting in permanent vision impairment/blindness.		
SKIN CONTACT: Direct contact may cause moderate skin irritation. Prolonged contact may result in skin damage.		
INHALATION: Not anticipated to be an exposure route. Inhalation of mists may cause moderate to severe respiratory tract irritation.		
INGESTION: Not anticipated to be an exposure route. May cause severe irritation of the gastrointestinal tract if ingested.		
SIGNS AND SYMPTOMS: This product will cause moderate to severe irritation if direct contact occurs. Symptoms will vary from mild irritation to severe burning, based on product concentration and duration of exposure.		
AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.		
OTHER HEALTH EFFECTS: This product contains Lithium, which may adversely affect a developing fetus.		
SECTION 12: ECOLOGICAL INFORMATION		
ECOTOXICITY: <i>Expected to have adverse impact on aquatic life based on product pH.</i>	DEGRADABILITY: N/E	BIOACCUMULATIVE POTENTIAL: N/E
SOIL MOBILITY: N/E	OTHER ADVERSE EFFECTS: None recognized.	
SECTION 13: WASTE DISPOSAL INFORMATION		
WASTE DISPOSAL INFORMATION: Consult local, state, and federal regulations for disposal information.		
SECTION 14: TRANSPORTATION INFORMATION		
HAZARDOUS/NON-HAZARDOUS MATERIAL: Not regulated by DOT.		
UN NUMBER: None.	HAZARD CLASS: N/A	PACKING GROUP: N/A
UN PROPER SHIPPING NAME: N/A		
ENVIRONMENTAL HAZARDS: None recognized.		
BULK TRANSPORTATION INFORMATION: None.		
SPECIAL PRECAUTIONS: Prevent product from freezing.		
SECTION 15: REGULATORY INFORMATION		
OTHER REGULATORY CONSIDERATIONS: None recognized.		
SECTION 16: OTHER INFORMATION		
PREPARATION DATE:	8/21/2015	
PREPARED BY:	Dave Carey	

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.
