

*** MATERIAL SAFETY DATA SHEET ***

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to implement the "Workplace Hazardous Materials Information System (WHMIS)". Also make this information available to any employee who requests it.

Date of preparation: 03/3/11

3900-662B

SECTION I PRODUCT IDENTIFICATION AND USE

Manufacturer : W. R. MEADOWS, INC.
Address : 300 INDUSTRIAL DRIVE
: HAMPSHIRE, IL 60140
Telephone # : (847) 214-2100
Emergency # : 1-800-424-9300 Chemtrec

- H M I S -
|Health : 2 |
|Fire : 1 |
|Reactivity : 0 |
|Person Protection : |

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)

Product Class : Class E, Corrosive Materials
Product Identification Number: 3900-662B
Product Identifier : REZI-WELD 3/2 GROUT PATCH - COMPONENT B
Product Use : Epoxy grout patch

SECTION II HAZARDOUS INGREDIENTS

Table with 9 columns: No. Hazardous Ingredient(s)*, CAS#, % By Weight, LD50, LC50, TLV/TWA, ACGIH TLV/Ceiling, TLV/STEL, SKIN. Rows include Diethylene Triamine, Tall Oil Fatty Acid "RPW", Triethylenetetramine, Tetraethylenepentamine, and Bisphenol-A.

* A more complete disclosure will be provided to a physician or nurse in the event of a medical emergency. None of the components of this product are recognized as carcinogenic.
Component data is defined in accordance with Sub-paragraph 13 (a) (i) to (iv) of the Hazardous Product Act.
N/A = Not applicable N/E = Not established * = Rat

SECTION III PHYSICAL DATA

Physical State : Liquid Vapour Density : > 1 (air =1)
Specific Gravity : 1.01 Evaporation Rate : <1 (ether = 1)
Product Odour/Appearance : Mild organic odour/amber colour Percent Volatile : N/A
Vapour Pressure : N/E Freezing Point : N/E
pH : N/E Boiling Point : 202 degrees C.
Odour Threshold : N/E

Coefficient of water/oil distribution: N/E

SECTION IV FIRE AND EXPLOSION DATA

Conditions of Flammability: Ignition sources. Autoignition temperature: N/E
Means of extinction: Water fog, foam, dry chemical, or Carbon Dioxide Sensitivity to mechanical impact: No
Flash point and method: 111 degrees C. Sensitivity to static discharge: No
Flammability limits: LEL: N/E UEL: N/E
Hazardous combustion products: Carbon Monoxide, Carbon Dioxide and incomplete combustion products.

SECTION V REACTIVITY DATA

Chemical stability: Stable
If no, under which conditions:
Incompatibility (materials to avoid): Avoid oxidizing materials.
Conditions of reactivity: None
Hazardous decomposition products: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

SECTION VI TOXICOLOGICAL PROPERTIES

Route(s) of entry: Inhalation, skin contact.
(Continued)

Date of preparation: 03/3/11

3900-662B

*** MATERIAL SAFETY DATA SHEET ***

Date of preparation: 03/3/11

3900-662B

Effect(s) of acute exposure to product:

EYE CONTACT: Based on the presence of component 4 this product is presumed to be corrosive to the eyes. Exposure may cause chemical burns and extensive corneal injury.

SKIN CONTACT: Based on the presence of component 1 this product is presumed to be corrosive to the skin and exposure may cause chemical burns. Absorption through the skin may result in symptoms of exposure as those described for inhalation and ingestion. Contact with the skin may result in skin sensitization to amines, polyamines, polyamides and related compounds. Individuals who have developed a skin sensitization can develop these symptoms as a result of contact with very small amounts of liquid material or as a result of exposure to vapour. This skin sensitization may be temporary or permanent. Once an individual is diagnosed as being sensitized, no further exposure can be permitted.

INHALATION: Exposure may produce irritation to the nose, throat, respiratory tract, and other mucous membranes. Based on the presence of component 1 as a result of repeated overexposures or exposure to a single large dose, certain individuals may develop lung sensitization (chemical asthma) to amines, polyamines, polyamides, and related compounds which will cause them to react to a later exposure at levels well below the TLV. Once an individual is diagnosed as being sensitized, no further exposure can be permitted. This lung sensitization may be either temporary or permanent.

INGESTION: Based on the presence of component 1 this product is corrosive and may cause chemical burns to the gastrointestinal tract.

SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea. Skin sensitization results in allergic dermatitis which may include rash, itching, hives and swelling of extremities. Lung sensitization results in asthma-like symptoms: chest tightness, shortness of breath, wheezing and coughing. These symptoms may be immediate or delayed up to several hours.

Exposure limits: See Section II.

Effect(s) of chronic exposure to product:

Carcinogenicity: No

Reproductive toxicity: Not established

Teratogenicity: Not established

Mutagenicity: Not established

Synergistic Properties: None known

SECTION VII PREVENTIVE MEASURES

Personal protective equipment: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

Engineering controls: Use ventilation as required to control vapour concentrations - at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

Leak and spill procedures: LARGE SPILLS>> Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapour cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. SMALL SPILLS>> Take up with an absorbent material and place in non-leaking containers.

Waste disposal: Observe all Provincial, Federal, State and local regulations regarding proper disposal.

Handling procedures/equipment: Handle as a corrosive product. Avoid direct contact.

Storage requirements: Store in a cool dry area, away from ignition sources. Keep containers closed when not in use.

Special shipping information: None

SECTION VIII FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with copious amounts of water for at least fifteen (15) minutes while holding eyelids open. Seek prompt medical attention.

SKIN CONTACT: Remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

INHALATION: If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

INGESTION: Do not induce vomiting. Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if the victim is conscious. Consult a physician, hospital, or poison control center and/or transport to an emergency facility immediately.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

SECTION IX PREPARATION OF MSDS

Prepared by: David Carey

Phone number: (847) 683-4500

Preparation date: 03/3/11

Product Identification Number: 3900-662B