

*** MATERIAL SAFETY DATA SHEET ***

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to implement the "Workplace Hazardous Materials Information System (WHMIS)". Also make this information available to any employee who requests it.

Date of preparation: 07/28/10

5210480-1

SECTION I PRODUCT IDENTIFICATION AND USE

Manufacturer : W. R. MEADOWS® OF CANADA

- H M I S -

Address : 70 Hannant Court
: Milton, ON L9T 5C1

|Health : 0|

|Fire : 0|

|Reactivity : 0|

|Person Protection : 0|

Telephone # : (905) 878-4122

Emergency # : 1-800-424-9300 Chemtrec

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)

Product Class : Division 7

Product Identification Number: 5210480-1

Product Identifier : PREMOULDED MEMBRANE® VAPOR SEAL WITH PLASMATIC® CORE (PMPC)

SECTION II-A HAZARDOUS INGREDIENTS

Table with 6 columns: No. Hazardous Ingredient(s)*, CAS#, % By Weight, SARA 313, VAPOR PRESSURE (MM Hg @ 20 C), LEL (@ 25 C). Rows include Petroleum Asphalt and Fiberglass Mat.

PREMOULDED MEMBRANE w/Plasmatic Core is defined by OSHA (29 CFR Part 1910) as an "Article". A manufactured item which is formed to a specific shape or design during manufacture which does not release or otherwise result in exposure to a hazardous chemical under normal conditions of use.

None of the components of this product are recognized as carcinogenic.

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372 chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

N/E = Not established

N/A = Not applicable

SECTION II-B OCCUPATIONAL EXPOSURE LIMITS

Table with 9 columns: No., PEL/TWA, OSHA PEL/CEILING, PEL/STEL, SKIN, TLV/TWA, ACGIH TLV/CEILING, TLV/STEL, SKIN. Rows include 1.5 mg/m³ and 2.5 mg/m³.

N/E = Not established

* = Asphalt fumes

+ = Respirable dust

** = Total dust

SECTION III PHYSICAL DATA

Table with 2 columns: Property (Boiling Point, Evaporation Rate, Vapor Density, pH Level) and Value (Not applicable or Black sheet).

SECTION IV HEALTH INFORMATION

EYE CONTACT: This product may cause mechanical irritation of the eyes.

SKIN CONTACT: This product may cause mechanical irritation of the skin.

INHALATION: This product is not hazardous via inhalation with normal product use.

INGESTION: This product has a low order of toxicity. If symptoms of gastrointestinal irritation develop, seek medical attention.

SIGNS AND SYMPTOMS: None known with normal product use.

AGGRAVATED MEDICAL CONDITIONS: None known with normal product use.

OTHER HEALTH EFFECTS: From skin painting studies in laboratory animals, it has been concluded that some asphalts may possess weak carcinogenic activity. This means that workers who practice poor personal hygiene, and who are repeatedly exposed by direct skin contact with petroleum asphalt over many years, may potentially be at risk of developing skin cancer. Intermittent or occasional skin contact with petroleum asphalt is expected to have serious health effects as long as personal hygiene measures, such as outlined in this material safety data sheet are followed. In addition, asphalt vapors may contain polycyclic hydrocarbons, some of which are known to be carcinogenic. Therefore, prolonged breathing of vapors should be avoided.

Date of Preparation : 07/28/10

*** MATERIAL SAFETY DATA SHEET ***

Date of preparation: 07/28/10

SECTION V EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with water to remove fibers

SKIN CONTACT: Flush with water to remove fibers. Wash affected area with soap and water if available.

INHALATION: None normally required.

INGESTION: None normally required.

SECTION VI FIRE AND EXPLOSION HAZARDS

FLAMMABILITY CLASSIFICATION

- **NFPA:** None

- **DOT:** None

FLASH POINT: Greater than 400 degrees F.

EXTINGUISHING MEDIA: Carbon Dioxide, water fog, foam, dry chemical

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS: None recognized

UNUSUAL FIRE AND EXPLOSION HAZARDS: None recognized

SECTION VII REACTIVITY

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIALS TO AVOID: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

SECTION VIII EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: None required with normal product use. If abraded, use of a dust filter respirator is recommended to prevent inhalation of fibers.

PROTECTIVE CLOTHING: Cotton work gloves/safety glasses

ADDITIONAL PROTECTIVE MEASURES: Not applicable

SECTION IX ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES: Not applicable; product is a solid.

WASTE DISPOSAL: This product may be considered a non-hazardous special waste in some locations if disposed of at a permitted landfill. Check Federal, State, and local regulations for compliance.

ADDITIONAL PROTECTIVE MEASURES: Not applicable

SECTION X ADDITIONAL PRECAUTIONS

Prevent contact with fire. Prevent "Job-site" damage.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data of the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.