

Date of preparation: 7-11-2007

6388000-4

**SECTION I**

**Manufacturer** : W. R. MEADOWS, INC.  
**Address** : 300 Industrial Drive  
 : Hampshire, Illinois 60140  
  
**Telephone #** : (847) 683-4500  
**Emergency #** : 1-800-424-9300 Chemtrec

**- H M I S -**  
 |Health : 1 |  
 |Flammability : 1 |  
 |Reactivity : 0 |  
 |Personal Protection : |

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,\*=Chronic)

**Product Class** : DIVISION 7  
**Mfg. code I.D.** : 6388000-4  
**Trade Name** : AIR-SHIELD LM

**SECTION II-A HAZARDOUS COMPONENTS**

No.	Component	CAS#	% by Weight	SARA 313	VAPOR PRESSURE (mm Hg @ 20 C)	LEL (@ 25 C)
1.	Petroleum Asphalt	8052-42-4	55-60	NO	N/A	N/A
2.	Petroleum Oil	64742-65-0	1-5	NO	N/A	N/A

None of the components of this product are recognized as carcinogenic. N/A: Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

**SECTION II-B OCCUPATIONAL EXPOSURE LIMITS**

No.	OSHA				ACGIH			
	PEL/TWA	PEL/CEILING	PEL/STEL	SKIN	TLV/TWA	TLV/CEILING	TLV/STEL	SKIN
1.	5 mg/m <sup>3</sup>	N/E	N/E	N/E	5 mg/m <sup>3</sup>	N/E	N/E	N/E
2.	5 mg/m <sup>3</sup> *	N/E	N/E	N/E	5 mg/m <sup>3</sup> **	N/E	10 mg/m <sup>3</sup> **	N/E

N/E: Not established \* = Mineral oil mist in air.

**SECTION III PHYSICAL DATA**

**Boiling Point** : 212 degrees F. **% Volatile by volume** : Not applicable  
**Evaporation Rate** : < 1 (ether = 1) **% Volatile by weight** : 25-30  
**Vapor Density** : > 1 (air = 1) **Weight per gallon** : 8.3 (Theoretical)  
**pH Level** : N/A **Appearance** : (Brown Liquid)

**SECTION IV HEALTH INFORMATION**

**EYE CONTACT:** This material may cause mild irritation.

**SKIN CONTACT:** Exposure may cause mild skin irritation. Prolonged or repeated contact may cause redness, burning, drying and cracking of the skin. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

**INHALATION:** Exposure is not expected via this route.

**INGESTION:** Single dose oral toxicity is low. Ingestion may cause irritation of the gastrointestinal tract and/or ulceration/burns in the throat and mouth.

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea.

**AGGRAVATED MEDICAL CONDITIONS:** Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

**OTHER HEALTH EFFECTS:** From skin-painting studies in laboratory animals, it has been concluded that some asphalts may possess weak carcinogenic activity. This means that workers who practice poor personal hygiene, and who are repeatedly exposed by direct skin contact with petroleum asphalt over many years, may potentially be at risk of developing skin cancer. Intermittent or occasional skin contact with petroleum asphalts is not expected to have serious health effects as long as good personal hygiene measures, such as those outlined in this material safety data sheet, are followed. In addition, asphalt vapors may contain polycyclic aromatic hydrocarbons, some of which are known to be carcinogenic. Therefore, prolonged breathing of vapors should be avoided.

Date of preparation: 7-11-2007

---

**SECTION V EMERGENCY AND FIRST AID PROCEDURES**

---

**EYE CONTACT:** If irritation or redness develops, move victim away from exposure source and into fresh air. Flush eyes with water for fifteen minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Wash affected areas with mild soap and water. Do not use petroleum solvents to remove solid.

**INHALATION:** If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

**INGESTION:** Dilute with liquid unless the victim is unconscious or very drowsy. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent aspiration into the lungs. Consult a physician, hospital, or poison control center and/or transport to an emergency facility immediately.

---

**SECTION VI FIRE AND EXPLOSION HAZARDS**

---

**FLAMMABILITY CLASSIFICATION** - NFPA: None.  
- DOT : Not regulated.

**FLASH POINT:** Greater than 200 degrees F.

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical, or Carbon Dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:** Clear fire area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH approved self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

---

**SECTION VII REACTIVITY**

---

**STABILITY:** Stable **HAZARDOUS POLYMERIZATION:** Will not occur

**CONDITIONS AND MATERIALS TO AVOID:** Avoid oxidizing materials and strong acids.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides and compounds of Nitrogen and Sulfur. Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

---

**SECTION VIII EMPLOYEE PROTECTION**

---

**RESPIRATORY PROTECTION:** Under normal use conditions, ventilation is not required. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

**PROTECTIVE CLOTHING:** Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

**ADDITIONAL PROTECTIVE MEASURES:** Eye wash fountains and safety showers should be available for use in an emergency.

---

**SECTION IX ENVIRONMENTAL PROTECTION**

---

**SPILL OR LEAK PROCEDURES: LARGE SPILLS>>** Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above.

**WASTE DISPOSAL:** Observe all Federal, State and local regulations regarding proper disposal.

---

**SECTION X ADDITIONAL PRECAUTIONS**

---

Containers may hold product residues even when empty. Wash with soap and water before eating, drinking, smoking or using toilet facilities.

---

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.