



CSI Code: 03050

No. 355

JULY 2004
(Supersedes September 2003)

LIN-SEAL® EMULSION

Curing and Sealing Compound

DESCRIPTION

LIN-SEAL EMULSION Curing and Sealing Compound is a true water-base, high solids solution of boiled linseed oil. LIN-SEAL EMULSION is a liquid membrane cure for freshly placed concrete that helps retain original moisture to aid cement hydration and assist in the development of high early and ultimate strengths. LIN-SEAL EMULSION is a single application penetrating sealer that protects existing concrete from the effects of de-icing chemicals. It also prevents map cracking, checking, spalling and scaling.

LIN-SEAL EMULSION appears milky-white in the container and when first applied, providing visual identification of covered area. Once applied and dried, it forms a clear transparent film, which provides an impermeable seal for optimum water retention.

USES

LIN-SEAL EMULSION Curing and Sealing Compound is ideal for use on bridge decks, parking garage decks, ramps or any other concrete surface exposed to water, salts or other destructive substances. LIN-SEAL EMULSION increases the durability of concrete to prolong its life.

FEATURES AND BENEFITS

- Increases durability to extend the useful life of concrete
- True water-base compound
- Ready-to-use
- Aids in moisture retention
- Use conventional commercial spraying equipment for quick, easy application
- Prevents scaling and spalling
- Adherence of subsequent paint applications is not affected
- VOC compliant...actual VOC content is less than 700 g/L

SPECIFICATIONS

ASTM C 309 Type 1, Class B*
AASHTO M 148 Type 1, Class B*
State D.O.T. Specifications
Boiled Linseed Oil: ASTM D 260
Fed. Spec. A-A-371 (formerly TT-L-190-D)
*With exemptions for drying time

PACKAGING

5 gallon (18.93 liter) Pails
55 gallon (208.20 liter) Drums

CONTINUED ON REVERSE SIDE...

APPLICATION

Surface Preparation...Surfaces to be sealed must be clean and dry. Remove all dirt, oil, grease, curing compounds and other substances that would prevent the proper penetration of the sealer. Application equipment must be clean and free of any previously used materials.

Mixing...For optimum performance, gentle mixing or agitation is recommended. DO NOT MIX EXCESSIVELY.

Application Method...LIN-SEAL EMULSION may be applied as soon as the free water disappears from the surface. Apply only in a temperature range of 40°F to 95°F (4°C to 35°C). Apply with conventional hand or power spray equipment...may also be applied with paving train equipment. Broom off puddles or any excess liquid. Old concrete should be treated annually.

Coverage...Apply at a rate of approximately 300 sq.ft./gal. (7.36 sq. m/L). A second application at approximately 600 sq. ft./gal. (14.7 sq. m/L) is recommended for increased protection and spall prevention.

Clean up...Use soap and water to clean tools and equipment.

PRECAUTIONS

DO NOT DILUTE. Do not store or apply at temperatures less than 40°F (4°C). Do not use on densely troweled surfaces or on surfaces where darkening of the concrete is undesirable. Do not mix "water-based" compounds with any compound containing solvent. LIN-SEAL EMULSION is intended for exterior use only in concrete exposed to de-icing salts and chemicals. KEEP FROM FREEZING.

HEALTH/SAFETY HAZARDS

Materials soaked with linseed oil (rags, absorbents, etc.) may spontaneously catch fire if improperly discarded. Immediately after use, all materials coming in contact with this product should be placed in sealed, water-filled containers. Refer to for complete health and safety information.

FOR THE MOST CURRENT PRODUCT INFORMATION,
VISIT OUR WEBSITE: www.wrmeadows.com



LIMITED WARRANTY

"W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order." Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As

W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.