

VOC LIMITS - North America (Except CA) *

Architectural Coatings

[Maximum Allowable VOC limit reported in: g/L (grams per liter), less water and exempt compounds]

State/District/County VOC RULE	U.S. EPA Federal (Current)	U.S. EPA (Amendment Changes) - [Proposed]	AZ (Maricopa County)	Canada [Proposed]	CT	DE	IL	IN [Proposed]	ME	MD	MA	NH	NJ	NY	OH	OTC **	OTC (Model Rule) - [Proposed]	PA	RI	VT	VA ***	Washington D.C.
Ozone Commission/ Consortium Member :	N/A	N/A	N/A	N/A	OTC	OTC	LADCO	LADCO	OTC	OTC	OTC	OTC	OTC	OTC	LADCO	(Northeast U.S. -- Coalition of 13 member States)	(Northeast U.S. -- Coalition of 13 member States)	OTC	OTC	OTC Member - but follows Federal EPA Rule	OTC	OTC
Rule Name/Number:	40 CFR Part 59	40 CFR Part 59	Rule 335	TBD	22a-174-41	Rule 41	Title 35 - Part 223	Title 326	Chapter 151	COMAR 26.11.33	310 CMR 7.25 (11) (b)	ENV-A-4200	Chapter 27 Sub-Chapter 23	Part 205	3745-113-01	Model Rule	Model Rule	Sub-Chapter C Section 5 130.600	No. 33	N/A	Chapter 40 Article 49	Chapter 7 Section 749
VOC Rule - Date Originally Implemented:	9/13/1999	Proposed for late 2011 - early 2012	7/13/1991	[1/1/2010]	5/1/2008	11/1/2006	7/1/2009	[1/1/2010]	1/1/2006	1/1/2005	1/1/2009	1/1/2007	1/1/2005	1/5/2005	1/1/2009	1/1/2003	Possibly 2012	1/1/2005	3/31/1994	N/A	3/24/2004	1/1/2005
VOC Rule - Date Last Amended:	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	6/4/2009	N/A	10/4/2006	N/A
"Sell-Through" Date ("ok" to sell if manufactured PRIOR to Rule Implementation Date):	Expired	TBD	Expired	1/1/2012 (1 year - except for Form Release - which will be 3 years.)	Indefinite	Indefinite	Indefinite	1/1/2013 (3 years)	Indefinite	Indefinite	1/1/2012	1/1/2010	Indefinite	Expired	12/31/2012	Expired	TBD	Indefinite	Indefinite	Expired	Expired	Indefinite
Concrete Curing Compounds	350	[350]	350	[350]	350	350	350	[350]	350	350	350	350	350	350	350	350	[350]	350	350	350	350	350
Concrete Curing Compounds for Roadways and Bridges	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.
Concrete Curing and Sealing Compounds	700	[350]	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	700	a.	a.
Concrete/Masonry Sealers	b.	[100]	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	[100]	b.	b.	b.	b.	b.
Concrete Protective Coatings	400	[100]	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	400	b.	b.
Concrete Surface Retarders	780	[780]	e.	[780]	780	780	780	[780]	780	780	780	780	780	780	780	780	[780]	780	780	780	780	780
Form Release Compounds	450	[250]	e.	[250]	250	250	250	[250]	250	250	250	250	250	250	250	250	[250]	250	250	450	250	250
Mastic Texture Coatings	300	[300]	e.	[300]	300	300	300	[300]	300	300	300	300	300	300	300	300	[100]	300	300	300	300	300
Primers and Undercoaters	350	[200]	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	350	f.	f.
Primers, Sealers, and Undercoaters	k.	k.	350	[200]	200	200	200	[200]	200	200	200	200	200	200	200	200	[100]	200	200	k.	200	200
Reactive Penetrating Sealers	e.	e.	e.	m.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	[350]	d.	d.	e.	d.	d.
Sealers (Including Clear Wood Sealers)	400	[200]	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	j.	f.	f.	400	f.	f.
Stains	550	[250]	350	[250]	250	250	250	[250]	250	250	250	250	250	250	250	250	[250]	250	250	550	250	250
Waterproof Mastic Coating	n.	n.	300	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.	n.
Waterproofing Membranes	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	[250]	b.	b.	b.	b.	b.
Waterproofing Sealers and Treatments	600	j.	400	[250]	250	250	250	[250]	250	250	250	250	250	250	250	250	j.	250	250	600	250	250
Waterproofing Sealers, Concrete/Masonry	g.	p.	g.	[400]	400	400	400	[400]	400	400	400	400	400	400	400	400	j.	400	400	g.	400	400
Default Category - Not Otherwise Defined- "Non-Flat : Non-Gloss"	250 (Default for all)	[150]	250 (Default for all)	[340] (Default for all)	150 (Default for all)	150 (Default for all)	150	[150]	150	150 (Default for all)	150	150 (Default for all)	150 (Default for all)	150	150	150	[150] (Default for all)	150 (Default for all)	150	250 (Default for all)	150 (Default for all)	150 (Default for all)
Default Category - Not Otherwise Defined- "Non-Flat: High Gloss"	N/A	[250]	N/A	N/A	N/A	N/A	250	[250]	250	N/A	250	N/A	N/A	250	250	250	N/A	N/A	250	N/A	N/A	N/A

- a. Category not included under this Rule. Use Concrete Curing Compound Category.
- b. Category not included under this Rule. Use Waterproofing Sealers, Concrete/Masonry.
- c. Category not included under this Rule. Use Default of 100 g/L maximum VOC.
- d. Category not included under this Rule. Use Default of 150 g/L maximum VOC.
- e. Category not included under this Rule. Use Default of 250 g/L maximum VOC.
- f. Category not included under this Rule. Use Primers, Sealers and Undercoaters.
- g. Category not included under this Rule. Use Waterproofing Sealers and Treatments.
- h. Category replaced by Concrete Masonry Sealers.
- i. Category eliminated.
- j. Category eliminated.
- k. Category not included under this Rule. Use either Primers and Undercoaters or Sealers.
- m. Category not included under this Rule. Use Default of 340 g/L maximum VOC.
- n. Category not included under this Rule. Use Mastic Texture Coatings.
- p. Category not included under this Rule. Use Sealers.

[] = Proposed VOC Limit and Proposed Rule Implementation, or Change Date.

* NOTE: This fact sheet is intended for general reference only and does not represent a full and complete statement of the technical or legal requirements associated with these regulations.

** Member States include: CT, DC, DE, MA, MD, ME, NH, NJ, NY, PA, RI and VT. Also covering the following counties in VA: Arlington, Fairfax, Loudoun, Prince William and Stafford; including the following cities in VA: Alexandria, Fairfax, Falls Church, Fredericksburg, Manassas and Manassas Park.

*** Covering the following counties in VA: Arlington, Fairfax, Loudoun, Prince William, Stafford - and the following cities in VA: Alexandria, Fairfax, Falls Church, Fredericksburg, Manassas and Manassas Park