

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC		
		CATEGORY	Meets Regulation	
PRODUCT	Actual VOC (g/L)		Yes	No
AIR BARRIERS, DAMPPROOFING, VAPORPROOFING, WATERPROOFING and ACCESSORIES				
AIR-SHIELD™ LM	0	Waterproofing Sealers and Treatments = 250 g/L max.	X	
AIR-SHIELD™ LM (ALL SEASON)	371	Waterproofing Sealers and Treatments = 250 g/L max.		X
AIR-SHIELD® LMP	90	Waterproofing Sealers and Treatments = 250 g/L max.	X	
CATALYTIC BONDING ASPHALT	182	Mastic Texture Coatings = 300 g/L max.	X	
DECK-O-SHIELD™	37	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
MEADOW-PRUF™ SEAMLESS	0	Waterproofing Sealers and Treatments = 250 g/L max.	X	
MEL-PRIME™ W/B	80	Primers, Sealers, and Undercoaters = 200 g/L max.	X	
MEL-PRIME™ VOC (Solvent Based)	439	Primers, Sealers, and Undercoaters = 200 g/L max.		X
MEL-ROL® LM	0	Waterproofing Sealers and Treatments = 250 g/L max.	X	
MEL-ROL® LM (ALL SEASON)	371	Waterproofing Sealers and Treatments = 250 g/L max.		X
POINTING MASTIC	251	Mastic Texture Coatings = 300 g/L max.	X	
SEALMASTIC™ SOLVENT - Spray	240	Waterproofing Sealers and Treatments = 250 g/L max.	X	
SEALMASTIC™ SOLVENT - Semi	240	Waterproofing Sealers and Treatments = 250 g/L max.	X	
SEALMASTIC™ SOLVENT - Trowel	221	Waterproofing Sealers and Treatments = 250 g/L max.	X	
SEALMASTIC™ EMULSION - Type I	0	Waterproofing Sealers and Treatments = 250 g/L max.	X	
SEALMASTIC™ EMULSION - Type II	0	Waterproofing Sealers and Treatments = 250 g/L max.	X	
SEALMASTIC™ EMULSION - Type III	0	Waterproofing Sealers and Treatments = 250 g/L max.	X	

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC		
PRODUCT	Actual VOC (g/L)	CATEGORY	Meets Regulation	
			Yes	No
CEMENTITIOUS REPAIR MORTARS/CONSTRUCTION GROUTS/LATEX ADHESIVES				
ACRY-LOK™	0	Primers, Sealers, and Undercoaters = 200 g/L max.	X	
DECK-O-WELD	0	Primers, Sealers, and Undercoaters = 200 g/L max.	X	
FLOOR-TOP STG PRIMER	0	Primers, Sealers, and Undercoaters = 200 g/L max.	X	
INTRALOK®	0	Primers, Sealers, and Undercoaters = 200 g/L max.	X	

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC		
		CATEGORY	Meets Regulation	
PRODUCT	Actual VOC (g/L)			Yes
CONCRETE CURING COMPOUNDS/CURING AIDS				
1100 (Clear and with Fugitive Dye)	23	Concrete Curing Compounds = 350 g/L max.	X	
1113 (Clear and with Fugitive Dye)	79	Concrete Curing Compounds = 350 g/L max.	X	
1130 (Clear and with Fugitive Dye)	99	Concrete Curing Compounds = 350 g/L max.	X	
1150 (Clear and with Fugitive Dye)	23	Concrete Curing Compounds = 350 g/L max.	X	
1150 (Clear and with Fugitive Dye)	23	Concrete Curing Compounds = 350 g/L max.	X	
1200 - White	75	Concrete Curing Compounds = 350 g/L max.	X	
1250 - White	62	Concrete Curing Compounds = 350 g/L max.	X	
1300 (Clear and with Fugitive Dye)	7	Concrete Curing Compounds = 350 g/L max.	X	
1325 (Clear and with Fugitive Dye)	9	Concrete Curing Compounds = 350 g/L max.	X	
1600 - White	18	Concrete Curing Compounds = 350 g/L max.	X	
1610 - White	13	Concrete Curing Compounds = 350 g/L max.	X	
1613- White	15	Concrete Curing Compounds = 350 g/L max.	X	
1625 - White	12	Concrete Curing Compounds = 350 g/L max.	X	
1635 - White	13	Concrete Curing Compounds = 350 g/L max.	X	
1635 - White	13	Concrete Curing Compounds = 350 g/L max.	X	
1640 - White	14	Concrete Curing Compounds = 350 g/L max.	X	
1645 - White	14	Concrete Curing Compounds = 350 g/L max.	X	
1650 - White	13	Concrete Curing Compounds = 350 g/L max.	X	
1655 - White	11	Concrete Curing Compounds = 350 g/L max.	X	

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC		
		CATEGORY	Meets Regulation	
PRODUCT	Actual VOC (g/L)		Yes	No
2245	169	Concrete Curing Compounds = 350 g/L max.	X	
2250	176	Concrete Curing Compounds = 350 g/L max.	X	
2255	179	Concrete Curing Compounds = 350 g/L max.	X	
CURE-TREAT™	0	Concrete Curing Compounds = 350 g/L max.	X	
CURE-TREAT™ RTU	0	Concrete Curing Compounds = 350 g/L max.	X	
DECK-O-TREAT	0	Concrete Curing Compounds = 350 g/L max.	X	
LIN-SEAL® EMULSION - Clear	29	Concrete Curing Compounds = 350 g/L max.	X	
LIN-SEAL® White	21	Concrete Curing Compounds = 350 g/L max.	X	
MED-CURE™	0	Concrete Curing Compounds = 350 g/L max.	X	
MED-CURE™ CONCENTRATE	0	Concrete Curing Compounds = 350 g/L max.	X	
CONCRETE CURING AND SEALING COMPOUNDS/SEALERS/DENSIFIER-HARDENERS				
BELLATRIX	58	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
CS-309™/25	691	Concrete Curing Compounds = 350 g/L max.		X
CS-309™/25 OTC	339	Concrete Curing Compounds = 350 g/L max.	X	
CS-309™/30	653	Concrete Curing Compounds = 350 g/L max.		X
DECK-O-GRIP®	673	Concrete Curing Compounds = 350 g/L max.		X
DECK-O-GRIP® W/B	11	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
DECRA-SEAL™	690	Concrete Curing Compounds = 350 g/L max.		X
DECRA-SEAL™ W/B	11	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
DUST-GUARD	0	Concrete Curing Compounds = 350 g/L max.	X	

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC		
		CATEGORY	Meets Regulation	
PRODUCT	Actual VOC (g/L)		Yes	No
EXPO-GLOSS® (BROWN)	697	Concrete Curing Compounds = 350 g/L max.		X
EXPO-GLOSS® (CLEAR)	689	Concrete Curing Compounds = 350 g/L max.		X
EXPO-GLOSS® W/B (BROWN)	47	Concrete Curing Compounds = 350 g/L max.	X	
EXPO-GLOSS® W/B (CLEAR)	38	Concrete Curing Compounds = 350 g/L max.	X	
LIN-SEAL® 50/50 (S/B)	378	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
LIQUI-HARD®	0	Default Category - "Flat" = 100 g/L max.	X	
LIQUI-HARD® ULTRA	0	Default Category - "Flat" = 100 g/L max.	X	
SEAL-CURE™ 309/25	644	Concrete Curing Compounds = 350 g/L max.		X
SEAL-CURE™ 309/30	619	Concrete Curing Compounds = 350 g/L max.		X
TIAH®	691	Waterproofing Concrete/Masonry Sealers = 400 g/L max.		X
VOCOMP®-20	4	Concrete Curing Compounds = 350 g/L max.	X	
VOCOMP®-25	46	Concrete Curing Compounds = 350 g/L max.	X	
VOCOMP®-30	61	Concrete Curing Compounds = 350 g/L max.	X	

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC		
		CATEGORY	Meets Regulation	
PRODUCT	Actual VOC (g/L)			Yes
CONCRETE FORM RELEASE AGENTS				
DUOGARD®	160	Form-Release Compounds = 250 g/L max.	X	
DUOGARD® II	55	Form-Release Compounds = 250 g/L max.	X	
DUOGARD® CITRUS	165	Form-Release Compounds = 250 g/L max.	X	
DUOGARD® NE	160	Form-Release Compounds = 250 g/L max.	X	
CONCRETE SET ACCELERATORS/SURFACE RETARDERS				
EVAPRE™	17	Default Category - "Flat" = 100 g/L max.	X	
EVAPRE™-RTU	0	Default Category - "Flat" = 100 g/L max.	X	
HYDRASET®	0	Default Category - "Flat" = 100 g/L max.	X	
HYDRASET-FREE®	0	Default Category - "Flat" = 100 g/L max.	X	
TOP-STOP™	0	Concrete Surface Retarders = 780 g/L max.	X	

* Member States include: CT, DC, DE, MA, MD, ME, NH, NJ, NY, PA, RI and VT. Also covering the following counties in VA: Arlington, Fairfax, Loudoun, Prince William and Stafford; including the following cities in VA: Alexandria, Fairfax, Falls Church, Fredericksburg, Manassas and Manassas Park.

NOTE: This fact sheet is intended for general reference only and does not represent a full and complete statement of the technical or legal requirements associated with these regulations.

VOC limits in: g/L (grams per liter),
less water and exempt compounds)

OTC - Architectural Coatings Regulation - Northeast U.S. *		OTC	
PRODUCT	Actual VOC (g/L)	CATEGORY	Meets Regulation
			Yes No

011510 (dmc)