

PRODUCT	Actual VOC (g/L)	ILLINOIS			INDIANA			MICHIGAN			OHIO			WISCONSIN			OTC		
		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation	
			Yes	No		Yes	No		Yes	No		Yes	No		Yes	No		Yes	No
AIR BARRIERS, DAMPPROOFING, VAPORPROOFING, WATERPROOFING and ACCESSORIES																			
AIR-SHIELD™ LM	0	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
AIR-SHIELD™ LM (ALL SEASON)	371	Waterproofing Sealers = 250 g/L max.		X	Waterproofing Sealers = 250 g/L max.		X	Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.		X	Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.		X
AIR-SHIELD® LMP	90	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
CATALYTIC BONDING ASPHALT	182	Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X	
DECK-O-SHIELD™	37	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete or Masonry Sealers = 400 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
MEADOW-PRUF™ SEAMLESS	0	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
MEL-PRIME™ WB	80	Primers, Sealers, and Undercoaters = 200 g/L max.	X		Primers, Sealers, and Undercoaters = 200 g/L max.	X		Primers, Sealers, and Undercoaters = 200 g/L max.	X		Primers, Sealers, and Undercoaters = 200 g/L max.	X		Primers, Sealers, and Undercoaters = 200 g/L max.	X		Primers, Sealers, and Undercoaters = 200 g/L max.	X	
MEL-PRIME™ VOC	439	Primers, Sealers, and Undercoaters = 200 g/L max.		X	Primers, Sealers, and Undercoaters = 200 g/L max.		X	Primers, Sealers, and Undercoaters = 200 g/L max.		X	Primers, Sealers, and Undercoaters = 200 g/L max.		X	Primers, Sealers, and Undercoaters = 200 g/L max.		X	Primers, Sealers, and Undercoaters = 200 g/L max.		X
MEL-ROL® LM	0	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
MEL-ROL® LM (ALL SEASON)	371	Waterproofing Sealers = 250 g/L max.		X	Waterproofing Sealers = 250 g/L max.		X	Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.		X	Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.		X
POINTING MASTIC	251	Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X		Mastic Texture Coatings = 300 g/L max.	X	
SEALMASTIC™ SOLVENT - Spray	240	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
SEALMASTIC™ SOLVENT - Semi	240	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
SEALMASTIC™ SOLVENT - Trowel	221	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
SEALMASTIC™ EMULSION - Type I	0	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
SEALMASTIC™ EMULSION - Type II	0	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
SEALMASTIC™ EMULSION - Type III	0	Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X		Waterproofing Sealers and Treatments = 600 g/L max.	X		Waterproofing Sealers = 250 g/L max.	X	
CEMENTITIOUS REPAIR MORTARS/CONSTRUCTION GROUTS/LATEX ADHESIVES																			

PRODUCT	Actual VOC (g/L)	ILLINOIS			INDIANA			MICHIGAN			OHIO			WISCONSIN			OTC		
		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation	
			Yes	No		Yes	No		Yes	No		Yes	No		Yes	No		Yes	No
1650 - White	13	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
1655 - White	11	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
2245	169	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
2250	176	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
2255	179	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
CURE-TREAT™	0	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
CURE-TREAT™ RTU	0	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
LIN-SEAL® EMULSION - Clear	29	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
LIN-SEAL® White	21	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
MED-CURE™	0	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
MED-CURE™ CONCENTRATE	0	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
CONCRETE CURING AND SEALING COMPOUNDS/SEALERS/DENSIFIER-HA																			
BELLATRIX	58	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete or Masonry Sealers = 400 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
CS-309™/25	691	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
CS-309™/25 OTC	339	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X	
CS-309™/30	653	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
DECK-O-GRIP®	673	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
DECK-O-GRIP® WB	11	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete or Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
DECRA-SEAL™	690	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
DECRA-SEAL™ WB	11	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
DUST-GUARD	0	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	

PRODUCT	Actual VOC (g/L)	ILLINOIS			INDIANA			MICHIGAN			OHIO			WISCONSIN			OTC		
		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation		CATEGORY	Meets Regulation	
			Yes	No		Yes	No		Yes	No		Yes	No		Yes	No		Yes	No
EXPO-GLOSS® (BROWN)	697	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.		X	Concrete Curing Compounds = 350 g/L max.		X
EXPO-GLOSS® (CLEAR)	689	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.		X	Concrete Curing Compounds = 350 g/L max.		X
EXPO-GLOSS® OTC (BROWN)	325	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
EXPO-GLOSS® OTC (CLEAR)	325	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X	
EXPO-GLOSS® W/B (BROWN)	47	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
EXPO-GLOSS® W/B (CLEAR)	38	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
LIN-SEAL® 50/50 (S/B)	378	Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X		Sealers = 400 g/L max.	X		Waterproofing Concrete/Masonry Sealers = 400 g/L max.	X	
LIQUI-HARD®	0	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	
LIQUI-HARD® ULTRA	0	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	
SEAL-CURE™ 309/25	644	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
SEAL-CURE™ 309/30	619	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
TIAH®	691	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X	Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.		X
VOCOMP®-20	4	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X	
VOCOMP®-25	46	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X	
VOCOMP®-30	61	Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X		Concrete Curing and Sealing Compounds = 700 g/l max.	X		Concrete Curing Compounds = 350 g/L max.	X	
CONCRETE FORM RELEASE AGENTS																			
DUOGARD®	160	Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X	
DUOGARD® II	55	Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X	
DUOGARD® CITRUS	165	Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X	
DUOGARD® NE	160	Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X		Form-Release Compounds = 450 g/L max.	X		Form-Release Compounds = 250 g/L max.	X	

		ILLINOIS			INDIANA			MICHIGAN			OHIO			WISCONSIN			OTC		
				Meets Regulation			Meets Regulation			Meets Regulation			Meets Regulation			Meets Regulation			
PRODUCT	Actual VOC (g/L)	CATEGORY	Yes	No	CATEGORY	Yes	No	CATEGORY	Yes	No	CATEGORY	Yes	No	CATEGORY	Yes	No	CATEGORY	Yes	No
CONCRETE SET ACCELERATORS/SURFACE RETARDERS																			
EVAPRE™	17	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	
EVAPRE™-RTU	0	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	
HYDRASET®	0	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	
HYDRASET-FREE®	0	Default Category = 100 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X		Default Category = 250 g/L max.	X		Default Category = 100 g/L max.	X	
TOP-STOP™	0	Concrete Surface Retarders = 680 g/L max.	X		Concrete Surface Retarders = 680 g/L max.	X		Concrete Surface Retarders = 680 g/L max.	X		Concrete Surface Retarders = 680 g/L max.	X		Concrete Surface Retarders = 680 g/L max.	X		Concrete Surface Retarders = 680 g/L max.	X	

Revision 3: 101210 (dmc)