

VOC LIMITS - CALIFORNIA AIR DISTRICTS \*

Architectural Coatings

[Maximum Allowable VOC limit reported in: g/L (grams per liter), less water and exempt compounds]

	CARB ** (California Air Resources Board)	CARB ** (California Air Resources Board) [Proposed Changes]	Antelope	BAAQMD (Bay Area)	BAAQMD (Bay Area) [Proposed Changes]	Butte	Colusa	El Dorado	Feather River	Imperial	Kern	Mojave	Monterey	Northern Sonoma	Placer	Sacramento	San Diego	San Joaquin	San Luis Obispo	Santa Barbara	Shasta	SCAQMD (South Coast)	Tehama	Ventura	Yolo-Solano
Rule Name/Number:	SCM	SCM	1113	Reg. 8 Rule 3	Reg. 8 Rule 3	230	2.26	215	3.15	424	410.1	1113	426	485	218	442	67	4601	433	323	3.31	1113	4.39	74.2	2.14
VOC Rule - Date Originally Implemented:	6/1/1977	[1/01/10]	7/1/1997	3/1/1978	[1/1/11]	7/1/1979	6/1/1979	9/1/1994	6/1/1991	11/1/1982	4/1/1972	2/1/1979	5/1/1979	4/2/2009	6/1/1979	12/1/1978	11/1/1977	4/1/1991	3/2/2009	10/1/1971	5/1/2002	9/1/1977	8/2/2009	6/1/1979	11/1/2001
VOC Rule - Date Last Amended:	10/1/2007	N/A	3/1/2003	7/1/2009	N/A	7/1/2002	7/1/2002	N/A	11/1/2002	2/1/2005	11/1/2006	2/1/2003	4/1/2002	N/A	12/1/2001	5/1/2001	12/1/2001	10/1/2001	N/A	11/1/2001	N/A	N/A	N/A	11/1/2001	N/A
"Self-Through" Date ("ok" to sell if manufactured PRIOR to Rule Implementation Date):	Expired	1/1/2013	Expired	7/1/2012	1/1/2014	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired	Expired
Concrete Curing Compounds	350	[350]	350	350	[350]	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	100	350	350	350
Concrete Curing Compounds for Roadways and Bridges	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.
Concrete Curing and Sealing Compounds	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.	a.
Concrete/Masonry Sealers	b.	[100]	b.	b.	[100]	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.
Concrete Protective Coatings	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.	b.
Concrete Surface Retarders	d.	c.	d.	d.	c.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	e.	d.	d.	d.
Form Release Compounds	250	[250]	250	250	[250]	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	e.	250	250	250
Mastic Texture Coatings	300	[100]	300	300	[100]	300	300	300	300	300	300	300	300	300	300	300	300	300	300	300	300	300	300	300	300
Primers and Undercoaters	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.	f.
Primers, Sealers, and Undercoaters	200	[100]	200	200	[100]	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	100	200	200	200
Reactive Penetrating Sealers	d.	[350]	d.	d.	[350]	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	e.	d.	d.	d.
Sealers (Including Clear Wood Sealers)	d.	c.	d.	d.	c.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	e.	d.	d.	d.
Stains	250	[250]	250	250	[250]	d.	d.	350	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	d.	100	d.	d.	d.
Waterproofing Membranes	g.	[250]	g.	g.	[250]	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.	g.
Waterproofing Sealers and Treatments	250	j.	250	250	j.	250	250	400	250	250	250	250	250	250	250	250	250	250	250	250	250	100	250	250	250
Waterproofing Sealers, Concrete/Masonry	400	h.	400	400	h.	400	400	g.	400	400	400	400	400	400	400	400	400	400	400	400	400	100	400	400	400
Default Category - Not Otherwise Defined- "Non-Flat : Non-Gloss"	150	[100]	150	150	[100]	150	150	250	150	150	150	150	150	150	150	150	150	150	150	150	150	250 (Default for all)	150	150	150
Default Category - Not Otherwise Defined- "Non-Flat: High Gloss"	250	[150]	250	250	[150]	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	N/A	250	250	250

- a. Category not included under this Rule. Use Concrete Curing Compound Category.
- b. Category not included under this Rule. Use Waterproofing Sealers, Concrete/Masonry.
- c. Category not included under this Rule. Use Default of 100 g/L maximum VOC.
- d. Category not included under this Rule. Use Default of 150 g/L maximum VOC.
- e. Category not included under this Rule. Use Default of 250 g/L maximum VOC.
- f. Category not included under this Rule. Use Primers, Sealers and Undercoaters.
- g. Category not included under this Rule. Use Waterproofing Sealers and Treatments.
- h. Category replaced by Concrete Masonry Sealers.
- j. Category eliminated.

[ ] = Proposed VOC Limit and Proposed Rule Implementation, or Change Date.  
 \* NOTE: This fact sheet is intended for general reference only and does not represent a full and complete statement of the technical or legal requirements associated with these regulations.  
 \*\* Covers all of CA - EXCEPT where a local AQMD (Air Quality Management District) Rule takes precedence.