



W. R. MEADOWS.

SEALTIGHT

A-500 OIL SPOT PRIMER

DATA SHEET NO. 2900-A500

DESCRIPTION

A-500 OIL SPOT PRIMER is a quick drying latex emulsion formulated to provide a protective barrier over oil, grease, gasoline, or chemical spills prior to application of sealer.

USES

A-500 OIL SPOT PRIMER can be used on any asphalt surface, including parking lots, driveways, airport runways and aprons, traffic safety islands, and golf cart paths.

PACKAGING

18.9 L (5 U.S. gallon) pails

COVERAGE

Coverage is approximately 4.8 m²/L (200 ft.²/gal).

PHYSICAL PROPERTIES

Color when dry Clear

PRECAUTIONS

Stir before using. Do not freeze. Do not store in direct sunlight. Do not store containerized sealer above 38° C (100° F). Containers should be closed when not in use.

Refer to Material Safety Data Sheet for complete health and safety information.

APPLICATION

Surface Preparation ... Scrape off and remove excess build up of oil, grease, or other chemicals before application.

Application Method ... Mix well before using. Dilute with water 2 to 1. On heavy oil spills, mix 1 to 1. Allow to completely cure before sealing. Do not apply when temperatures are below 10° C (50° F) or if rain is evident or forecast.

CLEANUP

While still wet, clean tools and equipment with soap and water. Use solvent if material has dried.

TO VERIFY MOST RECENT TECHNICAL DATA SHEET IS BEING USED, VISIT OUR WEBSITE:

www.wrmeadows.com

2009-02-28



W. R. MEADOWS OF WESTERN CANADA
38 Rayborn Crescent, St. Albert, AB T8N 5B4
Phone: (780) 458-8773 • Fax: (780) 458-1173

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
St. Albert, AB

www.wrmeadows.com