

## Canadian Architectural Coatings Regulation \*

PRODUCT CATEGORY	Product Category VOC Compliance Effective Date	Sell - Through Date	Maximum Allowable VOC **
Bituminous Roof Primer	9/9/2012	9/9/2014	350
Bituminous Roof Coating (not otherwise defined)	9/9/2012	9/9/2014	300
Concrete Curing Compound	9/9/2010	9/9/2012	350
Concrete Surface Retarder	9/9/2010	9/9/2012	780
Form Release Compound	9/9/2012	9/9/2014	250
Mastic Texture Coating	9/9/2010	9/9/2012	300
Waterproofing Sealer (not otherwise defined)	9/9/2010	9/9/2012	250
Waterproofing Sealer for Concrete or Masonry	9/9/2010	9/9/2012	400
Primer, Sealer or Undercoater (not otherwise defined)	9/9/2010	9/9/2012	200
Stain (not otherwise defined - including lacquer stains)	9/9/2010	9/9/2012	250
Traffic Marking Coating	9/9/2010	9/9/2012	450 ***

\* This document is intended for general reference only, and does not represent a full and complete statement of the technical or legal requirements associated with this regulation.

\*\* NOTE: The Canadian Architectural Coating Regulation is written such that each product category has a specific "effective date" and "sell-through date" for VOC Compliance.  
Please refer to the chart above for applicable VOC Compliance dates.

\*\*\* Per Canadian VOC Regulation, Section 4(1): A person must not use, during the period beginning on May 1 and ending on October 15, any traffic marking coating in which the VOC Concentration exceeds 150 g/L.  
(Begins on 9/9/2013)

VOC limits in: g/L (grams per liter),  
[less water and exempt compounds]