



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product: SPECTRUM 910 **Part Number:** 3855000
Manufacturer: W. R. MEADOWS OF ARIZONA **Address:** 4220 South Sarival Road
 Goodyear, Arizona 85338
Telephone: (623) 932-9383 **In case of emergency, dial (800) 424-9300 (CHEMTREC)**
Revision Date: 6/17/2016
Product Use: Liquid Stamp Protectant

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS		HAZARD STATEMENTS
Health	1	WARNING!
Flammability	2	Causes skin/eye irritation.
Reactivity	0	Flammable Liquid and vapor.
Personal Protection		Harmful if inhaled.
		May be fatal if ingested and enters airway.
		PRECAUTIONARY STATEMENTS
		Keep away from ignition sources.
		Use only in well-ventilated areas.
		Avoid breathing vapors and direct contact.
		Store in well-ventilated location.
		Wear appropriate personal protective equipment.
		Control vapors in confined spaces utilizing mechanical ventilation.



SECTION 3: HAZARDS COMPONENTS

<u>Chemical Name:</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>SARA 313</u>	<u>Vapor Pressure (mm Hg@20°C)</u>	<u>LEL (@25°C)</u>
1. Naphtha, Petroleum	64741-65-7	>90	No	0.8 psia @ 100F	1

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313." *N/E: Not Established*

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.
SKIN CONTACT: Wash affected areas with mild soap and water. Remove contaminated shoes/clothing. If symptoms persist, seek medical attention.
INHALATION: If respiratory symptoms develop move affected individual from exposure source and into fresh air. If symptoms persist, seek medical attention.
INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: 130 degrees F
EXTINGUISHING MEDIA: Water fog, foam, dry chemical.
CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products.
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid smoke inhalation. Use appropriate personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Avoid direct contact. Remove ignition sources. Dike and contain spilled material. Remove source of spill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact. For exterior use only. Avoid sources of ignition.
SAFE STORAGE: Keep containers closed when not in use. Keep away from ignition sources.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name:</u>	<u>OSHA</u>				<u>ACGIH</u>			
	<u>PEL</u>	<u>PEL/CEILING</u>	<u>PEL/STEL</u>	<u>SKIN</u>	<u>TWA</u>	<u>TLV/CEILING</u>	<u>TLV/STEL</u>	<u>SKIN</u>
1. Naphtha, Petroleum	N/E	N/E	N/E	No	300 ppm*	N/E	N/E	N/E

N/E: Not Established * : As Gasoline

ENGINEERING CONTROLS: Use with adequate ventilation. Use explosion-proof equipment.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 347 degrees F	VAPOR DENSITY: >1 (air=1)	% VOLATILE BY VOLUME: N/E
EVAPORATION RATE: <1 (Ether=1)	pH LEVEL: N/E	% VOLATILE BY WEIGHT: 100
WEIGHT PER GALLON: 6.33	PRODUCT APPEARANCE: Clear liquid	VOC CONTENT: 760 g/L

