



# SAFETY DATA SHEET

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product:** SEALMASTIC™ SEMI-MASTIC™ DAMPPROOFING **Part Number:** 6320055  
**Manufacturer:** W. R. Meadows®, Inc. **Address:** 300 Industrial Drive  
 Hampshire, Illinois 60140  
**Telephone:** (847) 214-2100 **In case of emergency, dial (800) 424-9300 (CHEMTREC)**  
**Revision Date:** 9/9/2014  
**Product Use:** Dampproofing for Concrete

## SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

<b>HMIS</b>		<b>HAZARD STATEMENTS</b>
Health	1	WARNING!
Flammability	2	Causes skin/eye irritation.
Reactivity	0	Flammable liquid and vapor.
Personal Protection		Harmful if inhaled.

May be fatal if ingested and enters airway.

**PRECAUTIONARY STATEMENTS:**  
 Use only in well-ventilated areas.  
 Avoid breathing vapors and direct contact.  
 Store in well-ventilated location.  
 Wear appropriate personal protective equipment.  
 Control vapors in confined spaces utilizing mechanical ventilation.



## SECTION 3: HAZARDS COMPONENTS

<u>Chemical Name:</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>SARA 313</u>	<u>Vapor Pressure (mm Hg@20°C)</u>	<u>LEL (@25°C)</u>
1. Mineral Spirits	64742-47-8	30-60	No	2.6	0.75
2. Petroleum Asphalt	8052-42-4	40-70	No	N/A	N/A

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313." *N/A: Not Applicable*

## SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.  
**SKIN CONTACT:** Wash affected areas with mild soap and water. Remove contaminated shoes/clothing. If symptoms persist, seek medical attention.  
**INHALATION:** If respiratory symptoms develop, move affected individual from exposure source and into fresh air. If symptoms persist, seek medical attention.  
**INGESTION:** Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

## SECTION 5: FIRE AND EXPLOSIVES HAZARDS

**FLASHPOINT:** 100 degrees F  
**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical.  
**CHEMICAL/COMBUSTION HAZARDS:** Carbon monoxide, carbon dioxide, oxides/compounds of nitrogen/sulfur, and incomplete combustion products.  
**PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT:** Avoid smoke inhalation. Use appropriate personal protective equipment.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** Avoid direct contact. Remove ignition sources. Dike and contain spilled material. Remove source of spill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal.

## SECTION 7: HANDLING AND STORAGE

**SAFE HANDLING PROCEDURES:** Avoid direct contact.  
**SAFE STORAGE:** Keep containers closed when not in use. Keep away from ignition sources.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name:</u>	<u>OSHA</u>				<u>ACGIH</u>			
	<u>PEL</u>	<u>PEL/CEILING</u>	<u>PEL/STEL</u>	<u>SKIN</u>	<u>TWA</u>	<u>TLV/CEILING</u>	<u>TLV/STEL</u>	<u>SKIN</u>
1. Mineral Spirits	100 ppm	500 ppm	N/E	No	100 ppm	N/E	200 ppm	N/E
2. Petroleum Asphalt	5 mg/m <sup>3</sup> *	N/E	N/E	No	5 mg/m <sup>3</sup> *	N/E	N/E	N/E

*N/E: Not Established*      \*: Asphalt Fumes

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses, chemical-resistant gloves.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>BOILING POINT:</b> 325 degrees F	<b>VAPOR DENSITY:</b> >1 (air=1)	<b>% VOLATILE BY VOLUME:</b> N/E
<b>EVAPORATION RATE:</b> <1 (Ether=1)	<b>pH LEVEL:</b> N/E	<b>% VOLATILE BY WEIGHT:</b> N/E
<b>WEIGHT PER GALLON:</b> 7.91	<b>PRODUCT APPEARANCE:</b> Black Liquid	<b>VOC CONTENT:</b> 240 g/L

# SAFETY DATA SHEET

Date of Preparation: 9/9/2014

Page 2 of 2

6320055

## SECTION 10: STABILITY/REACTIVITY

**STABILITY:** Stable.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS AND MATERIALS TO AVOID:** Oxidizing agents, strong acids, and strong alkalis.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, oxides/compounds of nitrogen/sulfur, and incomplete combustion products.

## SECTION 11: TOXICOLOGICAL INFORMATION

**EYE CONTACT:** Direct contact may cause mild to moderate irritation. Product vapors/mists may also cause irritation.

**SKIN CONTACT:** Direct contact may cause slight skin irritation. Prolonged/repeated contact may result in irritation/dermatitis.

**INHALATION:** Exposure may cause irritation of the nose, throat, respiratory tract, and other mucous membranes. Exposure to excessive vapor concentrations may cause signs of transient central nervous system depression (headache, fatigue, drowsiness, dizziness, loss of coordination).

**INGESTION:** May result in irritation of the gastrointestinal tract. Ingestion of excessive quantities may result in symptoms of transient central nervous system depression as noted above.

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation include tearing, reddening, and swelling. Symptoms of skin irritation include redness and swelling. Gastrointestinal irritation symptoms include nausea, vomiting, and abdominal discomfort. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of transient central nervous system depression include: headache, fatigue, drowsiness, dizziness, and loss of coordination.

**AGGRAVATED MEDICAL CONDITIONS:** Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

**OTHER HEALTH EFFECTS:** Some asphalts may possess weak carcinogenic activity. Occasional skin contact with petroleum asphalt is not expected to have serious health effects as long as good personal hygiene measures are followed.

## SECTION 12: ECOLOGICAL INFORMATION

**ECOTOXICITY:** N/E

**DEGRADABILITY:** N/E

**BIOACCUMULATIVE POTENTIAL:** N/E

**SOIL MOBILITY:** N/E

**OTHER ADVERSE EFFECTS:** None Recognized.

## SECTION 13: WASTE DISPOSAL INFORMATION

**WASTE DISPOSAL INFORMATION:** Fuel blending/recycling facility. Product is a hazardous waste (D001).

## SECTION 14: TRANSPORTATION INFORMATION

**HAZARDOUS/NON-HAZARDOUS MATERIAL:** Not regulated by DOT (Domestic Land Transportation).

**UN NUMBER:** None.

**HAZARD CLASS:** N/A

**PACKING GROUP:** N/A

**UN PROPER SHIPPING NAME:** N/A

**ENVIRONMENTAL HAZARDS:** None recognized.

**BULK TRANSPORTATION INFORMATION :** None.

**SPECIAL PRECAUTIONS:** None.

## SECTION 15: REGULATORY INFORMATION

**OTHER REGULATORY CONSIDERATIONS:** None recognized.

## SECTION 16: OTHER INFORMATION

**PREPARATION DATE:** 9/9/2014

**PREPARED BY:** Dave Carey

---

*The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.*

---