



# SAFETY DATA SHEET

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

<b>Product:</b>	<b>1100 RUBBERIZED CRACK FILLER</b>	<b>Part Number: 2900-1100</b>
<b>Manufacturer:</b>	<b>W. R. MEADOWS OF WESTERN CANADA</b>	<b>Address:</b> 21 Streambank Avenue Sherwood Park, AB T8H 1N1
<b>Telephone:</b>	(780) 400-1772	In case of emergency, dial (800) 424-9300 (CHEMTREC)
<b>Revision Date:</b>	1/4/2024	
<b>Product Use:</b>	Asphaltic Crack Filler	

### SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS	HAZARD STATEMENTS	
Health	<b>WARNING!</b>	
Flammability	Causes skin irritation. <b>(Category 2)</b>	
Reactivity	<b>PRECAUTIONARY STATEMENTS</b>	
Personal Protection	Avoid direct contact.	

### SECTION 3: HAZARDOUS COMPONENTS

<u>Chemical Name:</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>SARA 313</u>	<u>Vapor Pressure (mm Hg@20°C)</u>	<u>LEL (@25°C)</u>
1. Petroleum Asphalt	8052-42-4	65-70	No	N/A	N/A

*N/A: Not Applicable*

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

### SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Wash affected areas with mild soap and water.

**INHALATION:** Not expected to be an exposure route as supplied. If respiratory symptoms develop, seek medical attention.

**INGESTION:** Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

**MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC:** See Section Eleven for Symptoms/Effects.

### SECTION 5: FIRE AND EXPLOSIVES HAZARDS

**FLASHPOINT:** Product will not flash due to water content.

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical.

**CHEMICAL/COMBUSTION HAZARDS:** Oxides and compounds of nitrogen/sulfur, carbon monoxide/dioxide, and incomplete combustion products.

**PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT:** Avoid smoke inhalation. Use appropriate personal protective equipment.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** Avoid direct contact. Dike and contain spilled material. Remove source of spill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal. Clean-up materials will be classified as non-hazardous waste.

### SECTION 7: HANDLING AND STORAGE

**SAFE HANDLING PROCEDURES:** Avoid direct contact.

**SAFE STORAGE:** Prevent product from freezing.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name:</u>	<u>OSHA</u>				<u>ACGIH</u>			
	<u>PEL</u>	<u>PEL/CEILING</u>	<u>PEL/STEL</u>	<u>SKIN</u>	<u>TLV</u>	<u>TLV/CEILING</u>	<u>TLV/STEL</u>	<u>SKIN</u>
1. Petroleum Asphalt	5 mg/m <sup>3</sup> *	N/E	N/E	No	0.5 mg/m <sup>3</sup> *	N/E	N/E	N/E

**ENGINEERING CONTROLS:** None required under normal use conditions.      \*: Asphalt Fumes      N/E: Not Established

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses, chemical-resistant gloves.

