



# SAFETY DATA SHEET

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

<b>Product:</b>	<b>AIR-SHIELD™ ALUMINUM FLASHING</b>	<b>Part Number: 5116-000</b>
<b>Manufacturer:</b>	<b>W. R. MEADOWS OF CANADA</b>	<b>Address:</b> 70 Hannant Court Milton, Ontario Canada L9T 5C1
<b>Telephone:</b>	(905) 878-4122	In case of emergency, dial (800) 424-9300 (CHEMTREC)
<b>Revision Date:</b>	8/7/2020	
<b>Product Use:</b>	Air, Vapor, Liquid Moisture Barrier	

## SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS		
Health	0	AIR-SHIELD Aluminum Flashing--This is a manufactured article and under
Flammability	1	WHMIS criterion is not a controlled product.
Reactivity	0	
Personal Protection		

## SECTION 3: HAZARDS COMPONENTS

<u>Chemical Name:</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>SARA 313</u>	<u>Vapor Pressure (mm Hg@20°C)</u>	<u>LEL (@24°C)</u>
1. Petroleum Asphalt	8052-42-4	55-60	No	N/A	N/A

*N/A = Not Applicable*

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

## SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** Not expected to be an exposure route.  
**SKIN CONTACT:** Wash affected areas with soap and water if available.  
**INHALATION:** Not expected to be an exposure route.  
**INGESTION:** Not expected to be an exposure source.  
**MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC:** See Section Eleven for Symptoms/Effects.

## SECTION 5: FIRE AND EXPLOSIVES HAZARDS

**FLASHPOINT:** Not applicable; product is a solid.  
**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical.  
**CHEMICAL/COMBUSTION HAZARDS:** Oxides and compounds of nitrogen/sulfur.  
**PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT:** Avoid smoke inhalation. Use appropriate respiratory protection.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** Not applicable. Product is a solid.

## SECTION 7: HANDLING AND STORAGE

**SAFE HANDLING PROCEDURES:** Avoid direct contact.  
**SAFE STORAGE:** Prevent job-site damage.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name:</u>	OSHA				ACGIH			
	<u>PEL</u>	<u>PEL/CEILING</u>	<u>PEL/STEL</u>	<u>SKIN</u>	<u>TLV</u>	<u>TLV/CEILING</u>	<u>TLV/STEL</u>	<u>SKIN</u>
1. Petroleum Asphalt	5 mg/m <sup>3</sup> *	N/E	N/E	No	0.5 mg/m <sup>3</sup> *	N/E	N/E	N/E

*N/E = Not Established*      *\*: Asphalt Fumes*

**ENGINEERING CONTROLS:** None required under normal use conditions.  
**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses, chemical-resistant gloves.

