



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product:	HYDRASTOP™ SA	Part Number:	5117-850
Manufacturer:	W. R. MEADOWS OF CANADA	Address:	70 Hannant Court Milton, Ontario Canada L9T 5C1
Telephone:	(905) 878-4122	In case of emergency, dial (800) 424-9300 (CHEMTREC)	
Revision Date:	9/16/2019		
Product Use:	Waterproofing Membrane		

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS		
Health	1	This is a manufactured article and under WHMIS criterion is not a controlled product.
Flammability	1	
Reactivity	0	
Personal Protection		

SECTION 3: HAZARDS COMPONENTS

<u>Chemical Name:</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>SARA 313</u>	<u>Vapor Pressure (mm Hg@20°C)</u>	<u>LEL (@24°C)</u>
1. Petroleum Asphalt	8052-42-4	55-60	No	N/A	N/A

N/A = Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Not expected to be an exposure route under normal use conditions.
SKIN CONTACT: Not expected to be an exposure route under normal use conditions.
INHALATION: Not expected to be an exposure route.
INGESTION: Not expected to be an exposure source.
MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: Not applicable; product is a solid.
EXTINGUISHING MEDIA: Water fog, foam, dry chemical.
CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products.
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid smoke inhalation. Use appropriate respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Not applicable. Product is a solid.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact.
SAFE STORAGE: None

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name:</u>	OSHA				ACGIH			
	<u>PEL</u>	<u>PEL/CEILING</u>	<u>PEL/STEL</u>	<u>SKIN</u>	<u>TLV</u>	<u>TLV/CEILING</u>	<u>TLV/STEL</u>	<u>SKIN</u>
1. Petroleum Asphalt	5 mg/m ³ *	N/E	N/E	No	0.5 mg/m ³ *	N/E	N/E	N/E

ENGINEERING CONTROLS: None required under normal use conditions.
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, cotton work gloves
*N/E = Not Established *: Asphalt Fumes*

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A	VAPOR DENSITY: N/A	% VOLATILE BY VOLUME: N/A
EVAPORATION RATE: N/A	pH LEVEL: N/A	% VOLATILE BY WEIGHT: N/A
WEIGHT PER GALLON: N/A	PRODUCT APPEARANCE: Black Solid	VOC CONTENT: N/A
ODOR: Mild Asphaltic	ODOR THRESHOLD: N/D	MELTING/FREEZING POINT: N/D
FLASH POINT: See Section 5	FLAMMABILITY: N/D	UEL/LEL: N/D
VAPOR PRESSURE: N/D	RELATIVE DENSITY: N/D	SOLUBILITY: N/D
PARTITION COEFFICIENT: N/D	AUTOIGNITION TEMPERATURE: N/D	DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D		<i>N/D: Not Determined</i>

