



# SAFETY DATA SHEET

Page 1 of 3

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product:** SOF-SEAL® Component B **Part Number:** 4020-002  
**Manufacturer:** W. R. MEADOWS OF CANADA **Address:** 70 Hannant Court  
Milton, Ontario Canada L9T 5C1  
**Telephone:** (905) 878-4122 **In case of emergency, dial (800) 424-9300 (CHEMTREC)**  
**Revision Date:** 10/6/2022  
**Product Use:** Low Modulus Sealant

## SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS		HAZARD STATEMENTS
Health	1	<b>WARNING!</b>
Flammability	2	May cause damage to organs through prolonged/repeated exposures. <b>(Category 2)</b>
Reactivity	0	Flammable liquid and vapor. <b>(Category 3)</b>
Personal Protection		Causes skin irritation. <b>(Category 2)</b>
		Suspected of causing genetic defects. <b>(Category 2)</b>
		Harmful if inhaled. <b>(Category 4)</b>
		May be harmful if ingested and enters airway. <b>(Category 2)</b>
		<b>PRECAUTIONARY STATEMENTS</b>
		Use only in well-ventilated areas.
		Avoid breathing vapors/direct contact.
		Store in well-ventilated location.
		Wear appropriate personal protective equipment.
		Keep away from ignition sources.
		Control vapors in confined spaces utilizing mechanical ventilation.



## SECTION 3: HAZARDS COMPONENTS

<u>Chemical Name:</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>SARA 313</u>	<u>Vapor Pressure (mm Hg@20°C)</u>	<u>LEL (@25°C)</u>
1. Xylene	1330-20-7	1-5	Yes	6.6	1.1
2. Petroleum Asphalt	8052-42-4	25-30	No	N/A	N/A
3. Limestone	1317-65-3	25-30	No	N/A	N/A
4. Petroleum Distillate	68477-30-5	5-10	No	N/A	N/A

N/A: Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

## SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** Flush eyes with water for fifteen minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Wash affected areas with mild soap and water. Do not use petroleum solvents to remove. If symptoms persist, seek medical attention.

**INHALATION:** If symptoms persist move victim from exposure source and into fresh air. Treat symptomatically. If symptoms persist, seek medical attention.

**INGESTION:** Not anticipated to be an exposure route. Dilute by giving victim water or milk to drink. Do not induce vomiting. If vomiting, spontaneously occurs, keep the victim's head below the hips to prevent lung aspiration. Seek immediate medical attention.

**MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC:** See Section Eleven for Symptoms/Effects.

# SAFETY DATA SHEET

Date of Preparation: 10/06/22

Page 2 of 3

4020-002

## SECTION 5: FIRE AND EXPLOSIVES HAZARDS

**FLASHPOINT:** 33 °C

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical, or carbon dioxide.

**CHEMICAL/COMBUSTION HAZARDS:** Carbon monoxide, carbon dioxide, and incomplete combustion products.

**PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT:** Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure build-up, resulting in container rupture. Fire fighters should utilize full bunker ensemble when responding to a fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** Evacuate unnecessary personnel. Dike and contain. Remove/extinguish ignition sources.

Product is thick and will not flow quickly when spilled. Wear appropriate personal protective equipment. Place spill materials in sealed/marked containers for disposal.

## SECTION 7: HANDLING AND STORAGE

**SAFE HANDLING PROCEDURES:** Avoid direct contact. Avoid ignition sources. For exterior use only.

**SAFE STORAGE:** Keep containers closed when not in use. Store away from ignition sources.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name:	OSHA				ACGIH			
	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Xylene	100 ppm	N/E	N/E	N/E	100 ppm	N/E	150 ppm	N/E
2. Petroleum Asphalt	5 mg/m <sup>3</sup> *	N/E	N/E	N/E	5 mg/m <sup>3</sup> *	N/E	N/E	N/E
3. Limestone+	N/A	N/A	N/A	No	N/A	N/A	N/A	No
4. Petroleum Distillate	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E

+: Limestone is in solution. No exposure anticipated unless the product is dried/abraded.

\*: Asphalt Fumes

N/A: Not Applicable      N/E: Not Established

**ENGINEERING CONTROLS:** Use with adequate ventilation.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses, chemical-resistant gloves.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>BOILING POINT:</b> N/E	<b>VAPOR DENSITY:</b> >1 (Air=1)	<b>% VOLATILE BY VOLUME:</b> N/E
<b>EVAPORATION RATE:</b> < 1 (Ether=1)	<b>pH LEVEL:</b> N/A	<b>% VOLATILE BY WEIGHT:</b> 5.00 (Approximate)
<b>WEIGHT PER GALLON:</b> 9.98	<b>PRODUCT APPEARANCE:</b> Black Liquid	<b>VOC CONTENT:</b> 123 g/L
<b>ODOR:</b> Solvent	<b>ODOR THRESHOLD:</b> N/D	<b>MELTING/FREEZING POINT:</b> N/D
<b>FLASH POINT:</b> See Section 5	<b>FLAMMABILITY:</b> N/D	<b>UEL/LEL:</b> N/D
<b>VAPOR PRESSURE:</b> N/D	<b>RELATIVE DENSITY:</b> N/D	<b>SOLUBILITY:</b> N/D
<b>PARTITION COEFFICIENT:</b> N/D	<b>AUTOIGNITION TEMPERATURE:</b> N/D	<b>DECOMPOSITION TEMPERATURE:</b> N/D
<b>VISCOSITY:</b> N/D	N/A: Not Applicable      N/D: Not Determined      N/E: Not Established	

## SECTION 10: STABILITY/REACTIVITY

**STABILITY:** Stable.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS AND MATERIALS TO AVOID:** Oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of nitrogen/sulfur.

## SECTION 11: TOXICOLOGICAL INFORMATION

**EYE CONTACT:** Move victim from exposure source. Flush eyes with water for fifteen minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Wash affected areas with mild soap and water. If symptoms persist, seek medical attention.

**INHALATION:** Exposure to excessive vapor concentrations may result in transient central nervous system depression (headache, fatigue, drowsiness, loss of coordination). Intentional misuse by deliberately concentrating/inhaling vapors may be harmful or fatal. Repeated/prolonged occupational exposures to solvents may cause permanent brain and nervous system damage.

**INGESTION:** Not anticipated to be an exposure route. Ingestion may cause irritation of the gastrointestinal tract.

## SAFETY DATA SHEET

Date of Preparation: 10/06/22

Page 3 of 3

4020-002

### Section 11 continued

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation include tearing, reddening, and swelling. Symptoms of skin irritation include redness and swelling. Gastrointestinal irritation symptoms include nausea, vomiting, and abdominal discomfort. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of transient central nervous system depression include: headache, fatigue, drowsiness, dizziness, and loss of coordination.

**AGGRAVATED MEDICAL CONDITIONS:** Pre-existing skin, eye, and respiratory disorders may be aggravated by product exposure.

**OTHER HEALTH EFFECTS:** Some asphalts and aromatic oils may contain polycyclic aromatic hydrocarbons, some of which have been shown to cause skin cancer in laboratory animals under conditions of poor personal hygiene. Intermittent or occasional contact is not expected to present a cancer hazard, as long as good personal hygiene measures are followed. Fumes/vapors from these materials may also contain polycyclic aromatic hydrocarbons, so inhalation of these materials should be avoided. Both xylene and aromatic oils have been found to cause the following effects on laboratory animals: liver/kidney effects, blood abnormalities, effects on the spleen, testes, nervous system, adrenals, cardiovascular systems, and harm to the fetus. The relevance to humans is unknown.

### SECTION 12: ECOLOGICAL INFORMATION

**ECOTOXICITY:** N/E

**DEGRADABILITY:** N/E

**BIOACCUMULATIVE POTENTIAL:** N/E

**SOIL MOBILITY:** N/E

**OTHER ADVERSE EFFECTS:** N/E

N/E: Not Established

### SECTION 13: WASTE DISPOSAL INFORMATION

**WASTE DISPOSAL INFORMATION:** Product will be classified as a hazardous waste (D001). Suitable for fuel blending.

### SECTION 14: TRANSPORTATION INFORMATION

**HAZARDOUS/NON-HAZARDOUS MATERIAL:** Hazardous.

**UN NUMBER:** 1999

**HAZARD CLASS:** 3

**PACKING GROUP:** 3

**UN PROPER SHIPPING NAME:** Tars, Liquid.

**ENVIRONMENTAL HAZARDS:** None recognized.

**BULK TRANSPORTATION INFORMATION:** Not applicable. Product not shipped in bulk configuration.

**SPECIAL PRECAUTIONS:** None.

### SECTION 15: REGULATORY INFORMATION

**OTHER REGULATORY CONSIDERATIONS:** None.

### SECTION 16: OTHER INFORMATION

**PREPARATION DATE:** 10/6/2022

**PREPARED BY:** Dave Carey

*The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.*