



MasterFormat: 03 39 23

AUGUST 2023
(Supersedes May 2020)

1610-WHITE

Water-Based, Wax-Based Concrete Curing Compound

DESCRIPTION

1610-WHITE water-based, wax-based concrete curing compound, when properly applied, provides a premium-grade film, which optimizes water retention. The white pigment reflects the sun's rays to help keep the concrete surface cooler and to prevent excessive heat buildup.

USES

1610-WHITE is ideal for application on exterior, horizontal surfaces, such as highways, airports and street and curb paving. The product provides excellent curing properties when protection from the sun's heat is desired.

FEATURES/BENEFITS

- When properly applied, provides a premium-grade film, which optimizes water retention.
- Protects by reflecting the sun's rays to keep the concrete surface cooler and prevent excessive heat buildup, which can cause thermal cracking.
- Furnished as a ready-to-use, true water-based compound.
- Produces hard, dense concrete ... minimizes hair-checking, thermal cracking, dusting, and other defects.
- Offers a compressive strength significantly greater than improperly cured or uncured concrete.
- Improves tensile strength for greater resistance to cracking and surface crazing.
- Minimizes shrinkage.
- Applies quickly and easily with conventional commercial spray equipment.
- VOC compliant.

PACKAGING

5 Gallon (18.9 L) Pails
55 Gallon (208.2 L) Drums
275 Gallon (1041 L) Totes

COVERAGE

Approximately 200 ft.²/gal. (4.91 m²/L). Coverage is approximate and may vary depending on surface finish/texture, concrete condition, climatic conditions, etc. Always apply to a test area first to determine actual coverage rate before full-scale application.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 40° - 90° F, optimum performance and best use is obtained within one year of date of manufacture.

SPECIFICATIONS/STANDARDS

- ASTM C309, Type 2, Class A
- AASHTO M 148, Type 2, Class A
- Arkansas DOT: Section 501.02(i)(2)
- Colorado DOT: Section 711.01
- Kansas DOT: Section 1404
- Iowa DOT: Section 4105.05
- Louisiana DOT: Section 1011.01.1
- Missouri DOT: Section 1055.2
- Texas TxDOT DMS-4650
- West Virginia DOT: Section 707.9
- Indiana DOT: Section 912.01(e)
- Complies with all current federal, state, and local maximum allowable VOC requirements, including National AIM, LADCO, and OTC Phase I and II.

TECHNICAL DATA

VOC Content: 38 g/L

APPLICATION

Mixing ... Any settlement can be re-dispersed with gentle agitation prior to use. **CAUTION: TO AVOID FOAMING, DO NOT MIX EXCESSIVELY.**

CONTINUED ON REVERSE SIDE ...

W. R. MEADOWS, INC.

P.O. Box 338 • HAMPSHIRE, IL 60140-0338
Phone: 847/214-2100 • Fax: 847/683-4544
1-800-342-5976
www.wrmeadows.com • info@wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA
FORT WORTH, TX / BENICIA, CA / POMONA, CA
GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB

Application Method ... Application equipment must be clean and free of any previously used materials. Spray on in one even coat with a hand or power sprayer as soon as the surface water disappears from horizontal concrete surfaces. Use a sprayer, such as Chapin 1949, and a spray nozzle that produces a flow of 0.5 GPM under 40 psi of pressure. Do not allow spray nozzle to drip.

Drying Time ... Approximately two hours. Restrict foot traffic for at least four hours.

Cleanup ... Prior to drying, cleanup can be accomplished with soap and water. Once dried, use mineral spirits or other suitable petroleum solvent.

PRECAUTIONS

KEEP FROM FREEZING. Do not apply when the temperature of the concrete is less than 40° F (4.4° C). DO NOT MIX WITH COMPOUNDS CONTAINING SOLVENT. DO NOT ADD OR DILUTE WITH ANY OTHER COMPOUND. Do not use on surfaces that are later to be painted, tiled, hardened, sealed, or treated in any manner. Do not use on patios, sidewalks, or other areas where there is typically no wheel traffic to abrade the white film surface. Not recommended for use on residential driveways.

HEALTH AND SAFETY

Direct contact may result in mild irritation. Refer to Safety Data Sheet for complete health and safety information.

For most current data sheet, LEED information, and SDS, visit www.wrmeadows.com.



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control

over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.