



DATA SHEET NO. 2900-A625

A-625 FAST DRY

Additive for TRMSS and Asphalt-Based Sealers

DESCRIPTION

A-625 FAST DRY is a specially blended copolymer emulsion additive containing fast drying chemicals that modifies tire rubber modified surfaces and asphalt emulsion sealers and increases tensile strength and high viscosity buildup.

USES

When specifications demand traffic be opened up quickly, use A-625 FAST DRY on any asphalt surfaces, such as commercial and industrial parking lots, fast food and mall lots, and driveways. It is recommended for faster curing of asphalt-based or tire-modified surface sealers. It reduces tracking and power steering scuff marks. A-625 FAST DRY is user friendly and complies with all VOC emissions and EPA standards.

FEATURES/BENEFITS

- Outstanding toughness and adhesion.
- Better suspension of the aggregates.
- Resistant to oils, fuels, grease, and chemicals.
- Provides faster curing times.

PACKAGING

18.9 L (5 U.S. Gallon) Pail

COVERAGE

Recommended mix formulation:

3.78 L (1 gal.) A-625 FAST DRY per 208 L (55 U.S. gal) sealer.

TECHNICAL DATA

Weight/Gallon @ 77° F (ASTM D1010, (lb) 8.50 - 8.80 (3.8 - 3.9 Kg)

Nonvolatile % (ASTM D2939) 52 - 56

Viscosity @ 77° F (Krebs Stormer Unit) 60 - 65

Flammability Non-Flammable

PH 5.00 - 6.00

Storage Life One - Two Years

APPLICATION

Surface Preparation ... Surface must be free from dirt, dust, and oil. Treat oil, grease, and gasoline spots with A-500 OIL SPOT PRIMER.

Application Method ... Mix well before using. The amount will vary depending upon the type of end use or specifications.

When using a mechanical sprayer or squeegee-type machine, add sealer and proper amount of water (**when using TRMSS**). Start agitator and slowly add recommended amount of A-625 FAST DRY and mix to a uniform consistency. Aggregate, if being used, is added last, and mixed thoroughly before application.

Cleanup ... Wash tools with water.

PRECAUTIONS

Do not freeze. Keep out of reach of children. Do not store in direct sunlight. Container should be closed when not in use.

Refer to Safety Data Sheet for complete health and safety information.

MASTERFORMAT NUMBER AND TITLE

32 01 13.62 – Asphalt Surface Treatment

LEED INFORMATION

May help contribute to LEED credits:

- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

For most recent data sheet, further LEED information, and SDS, visit www.wrmeadows.com.



2015-12-15

W. R. MEADOWS® OF CANADA

70 Hannant Court, Milton, ON L9T 5C1

38 Rayborn Crescent, St. Albert, AB T8N 4B1

(800) 342-5976

Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
St. Albert, AB

www.wrmeadows.com