



DATA SHEET NO. 3040-050

X-FOAM™

Flexible, Lightweight, Concrete Expansion Joint Filler

DESCRIPTION

X-FOAM expansion joint filler is a flexible, lightweight, non-staining, polypropylene, closed-cell expansion joint filler. It is a chemical-resistant, ultraviolet stable, non-absorbent, low density, cost-effective, compressible foam that offers an extended service life in both interior and exterior applications.

USES

X-FOAM is ideal for use as an expansion, contraction, and/or isolation joint in swimming pool decks, curb and gutter work, floor slabs, pavement patch repair, sidewalks, driveways, plazas, parking decks, highways, and airport runways. The use of X-FOAM expansion joint combined with proper sealing and joint design per American Concrete Institute guidelines can help reduce unwanted cracking and early joint edge deterioration.

FEATURES/BENEFITS

- Flexible, lightweight, and can be formed around curved objects.
- Easy to carry.
- Easy to install.
- Can be used in interior or exterior applications.
- May be easily scored with a razor tool to create a void for POURTHANE® or DECK-O-SEAL®

PACKAGING

Thickness	Widths	Standard Lengths
12.7 mm (1/2")	76.2, 88.9, 101.6, 152.4, 203.2 mm (3", 3.5", 4", 6", 8")	1.5, 3.05 m (5', 10')

*Special sizes available upon request.

SPECIFICATIONS

- ASTM D8139-17: Standard Specification for Semi-Rigid, Closed-Cell Polypropylene Foam, Preformed Expansion Joint Fillers for Concrete Paving and Structural Construction
- ASTM D1751 (Extrusion, Compression Recovery, Water Absorption)

TECHNICAL DATA

Test Method	Specification	Result
Compressive Strength per ASTM D545	0.2 - 0.4 MPa (30 - 60 psi)	>0.2, <0.4 MPa (>30, <60 psi)
Recovery per ASTM D545	≥ 80%	Pass
Extrusion per ASTM D545	≤ 2.5 mm (≤ 0.10")	Pass
Density per ASTM D545	≥ 40 kg/m ³ (≥ 3.5 lb./ft. ³)	Pass
Water Absorption @ 24 Hours per ASTM D545	≤ 1%	Pass
Heat Resistance per ASTM D5249	No observable shrinkage or disintegration	No observable shrinkage or disintegration
Freeze-Thaw Resistance per ASTM C666 Observations @ 300 cycles	No visual change	No visual change
UV Weathering per ASTM D4329 Observed Change/Cracks @ 1000 hours	No observable change or cracks	No observable change or cracks

APPLICATION

Attach X-FOAM securely to the existing concrete slab, coping, or form with tape or mechanical fasteners prior to pouring the next slab. Make sure that X-FOAM is level with the desired slab surfaces before finishing.

MASTERFORMAT NUMBER AND TITLE

03 15 00 - Concrete Accessories

For most recent data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

2022-06-09

W. R. MEADOWS® OF CANADA

70 Hannant Court, Milton, ON L9T 5C1
21 Streambank Ave., Sherwood Park, AB T8H 1N1
(800) 342-5976
Montreal Sales: (514) 865-2406

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
Sherwood Park, AB
www.wrmeadows.com
info@wrmeadows.com

® SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings