



DATA SHEET NO. 3050-340

SURE-STEP™ Slip-Resistant Additive

DESCRIPTION

SURE-STEP slip-resistant additive is a finely ground polymer material for addition to concrete sealers for slip resistance. This additive can be added to most film-forming water-based and solvent-based sealers, including the CS-309™, SEAL-CURE™, and VOCOMP® series, as well as HIAC™ and DECRA-SEAL™ from W. R. MEADOWS. Please consult sealer manufacturer prior to using, if using a product not listed above.

SURE-STEP provides improved abrasion resistance and is more comfortable to bare feet on treated surfaces than sand or aggregate additives. The product's low density and insolubility characteristics will help reduce settling and provide optimum performance in its various applications without changing the viscosity. Due to its low density, SURE-STEP stays suspended in thin materials.

USES

SURE-STEP is perfect for use on areas where a slip-resistant surface is desired. This includes walkways, driveways, garage floors, patios and other surfaces.

FEATURES/BENEFITS

- Provides improved abrasion resistance.
- Does not change viscosity.
- Allows easy cleaning of the surface.
- Provides slip-resistance properties on surface without sacrificing comfort for barefoot traffic.

PACKAGING

453.6 G (16 Oz.) Containers

COVERAGE

Recommended for 18.9 litre (5 U.S. gallon) pails.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C (40° - 90° F), optimum performance and best use is obtained within two years of date of manufacture.

APPLICATION

Surface Preparation ... Follow surface preparation directions of sealer being applied.

Application Method ... SURE-STEP is designed to be incorporated into a suitable concrete sealer. Minimum addition ratio is 453.6 g (16 oz.) per 18.9 L (5 U.S. gallon) pail. Additional SURE-STEP can be added, depending on the desired texturing effect. Do not exceed 226.8 g (8 oz.) per 3.79 L (1 U.S. gallon). Stir, while adding SURE-STEP to the container of sealer. The product may float at first, but once it has wet out, it will mix in easily. In thinner products, occasional stirring during application may be required to keep the particles well suspended within the coating. It is recommended that when mixing SURE-STEP into unfamiliar sealers that a small test batch be mixed, followed by a small test application.

Drying Time ... Follow directions of sealer being applied.

Clean Up ... Follow directions of sealer being applied.

PRECAUTIONS

SURE-STEP will increase the texturing effect of a sealer, but the addition of the slip resistant additive should not be considered non-skid, anti-skid, or non-slip. Under some conditions, the granules may be visible. Depending on the surface, this may alter colour or dull the surface. A small application test section is recommended.

Continued over ...

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
38 Rayborn Crescent, St. Albert, AB T8N 4B1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
St. Albert, AB
www.wrmeadows.com

HEALTH AND SAFETY

SURE-STEP is not hazardous and does not contain silica, but should be treated as a nuisance dust while incorporating it into its intended vehicle. Use with adequate ventilation. Use appropriate, properly fitted respirator protection filter apparatus and avoid breathing dust and particles. If dizziness, headache or eye watering occurs, get to fresh air; leave area immediately. In case of eye contact, flush with large amounts of water for at least 15 minutes. Seek medical attention if irritation persists. Do not take internally. If swallowed, seek medical attention immediately. Keep out of reach of children. Close container after each use. Use protective clothing to avoid contact with skin and eyes. Refer to Safety Data Sheet for complete health and safety information.

MASTERFORMAT NUMBER AND TITLE

03 05 00 - Common Work Results for Concrete

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management

For most recent data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

2017-11-09



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.