



W. R. MEADOWS.

SEALTIGHT

DATA SHEET NO. 3150-121

FIBRE EXPANSION JOINT
Multi-Purpose, Expansion-Contraction Joint Filler

DESCRIPTION

FIBRE EXPANSION JOINT is composed of cellular fibres securely bonded together and uniformly saturated with asphalt to assure longevity. Wherever a cost-effective joint filler is required. FIBRE EXPANSION JOINT meets the need. Manufactured and marketed by W. R. MEADOWS since the early 1930s, FIBRE EXPANSION JOINT is backed by over 80 years of proven application experience. FIBRE EXPANSION JOINT is versatile, resilient, flexible, and non-extruding. When compressed to half of its original thickness, it will recover to a minimum of 70% of its original thickness. FIBRE EXPANSION JOINT will not deform, twist, or break with normal on-the-job handling. Breakage, waste, and functional failure resulting from the use of inferior, foreign fibre materials can cost you time and dollars and can result in a substandard finished job, generating costly call backs and rework expenses. However, the purchase and installation of FIBRE EXPANSION JOINT (a small segment of the total project's cost) contributes to both the final cost efficiency and functional success, far greater in proportion than its original cost.

Representative United States patents: USPNs 7,815,722; 8,057,638; 8,038,845; and D558,305. (See also www.wrmeadows.com/patents for further patent/intellectual property information.)

USES

FIBRE EXPANSION JOINT is ideal for use on highways, streets, airport runways, sidewalks, driveways, flatwork and scores of commercial and industrial applications subject to pedestrian and vehicular traffic.

FEATURES/BENEFITS

- Provides the ideal product for the majority of all expansion/contraction joint requirements.
Non-extruding ... versatile ... offers a minimum 70% recovery after compression.
This tough, lightweight, easy-to-use, semi-rigid joint filler is available in strips and shapes fabricated to your requirements.
Easy to cut ... dimensionally stable ... not sticky in summer or brittle in winter.
Provides neat, finished joints requiring no trimming.
Often copied ... but never equalled.

- Remains the standard of the industry today ... with over 80 years of proven and satisfactory performance.
Can be punched for dowel bars and laminated to thicknesses greater than 25.4 mm (1").

SPECIFICATIONS AND SIZE INFORMATION

Table with 5 columns: Conforms to or meets:, Thickness, Slab Widths, Standard Lengths, Weight. It lists various standards like AASHTO M 213, ASTM D1751, and CRD-C 508, along with their respective dimensions and weights.

APPLICATION

FIBRE EXPANSION JOINT is positioned against the forms, at interrupting objects or columns, and against abutting structures prior to the placement of concrete. FIBRE EXPANSION JOINT should be installed 12.7 mm (1/2") below the concrete surface to accept a joint sealant which will provide for maximum protection from water infiltration and weathering, in addition to keeping the joint free from incompressibles. SNAP-CAP® from W. R. MEADOWS is recommended to create the reservoir for the joint sealant and the use of POURTHANE SL, POURTHANE NS, or DECK-O-SEAL as the sealant to protect the joint. Before sealing, slide SNAP-CAP over the top of the expansion joint. Place the concrete and screed to finish grade, as usual. When concrete is cured, insert a screwdriver through the top of SNAP-CAP, pull free and discard. In applications where one of the above-mentioned joint sealants is used without SNAP-CAP, W. R. MEADOWS recommends the use of KOOL-ROD or a bond-breaker tape to isolate FIBRE EXPANSION JOINT from the joint sealant material. SOF-SEAL® or any hot-applied sealant, such as HI-SPEC®, can be used to protect the joint. In this case, the use of SNAP-CAP, KOOL-ROD, or a bond-breaker tape is not necessary. Simply apply the sealant directly over FIBRE EXPANSION JOINT.

MASTERFORMAT NUMBER AND TITLE

03 15 00 - Concrete Accessories

W. R. MEADOWS OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
21 Streambank Ave., Sherwood Park, AB T8H 1N1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
Sherwood Park, AB
www.wrmeadows.com

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management

For most current data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

2018-06-12



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.