



W. R. MEADOWS

SEALTIGHT

DATA SHEET NO. 3466-000

DECK-O-GRIP® W/B

Water-Based, Acrylic, Slip-Resistant Concrete Deck Treatment

DESCRIPTION

DECK-O-GRIP W/B is a non-yellowing, water-based, blended, polymer-based, high solids sealer for decorative concrete. The product is clear, transparent, and easy to apply. DECK-O-GRIP W/B also offers greatly improved chemical resistance when compared to standard acrylic-only based curing and sealing compounds. The product has been formulated to seal and protect decorative coloured concrete by producing a hard, yet flexible, clear film. The compound contains a slip-resistant additive, which produces a slip-resistant surface, for use on traditionally slippery areas. This product is specifically formulated for the residential decorative concrete market.

USES

DECK-O-GRIP W/B is designed for various applications, including exterior concrete surfaces, driveways, patios, swimming pool areas, and exposed aggregate, as well as any exterior surface where protection and sealing of concrete is desired. The use of DECK-O-GRIP W/B on any exterior concrete surface provides a durable, long-lasting finish that has improved resistance to chemicals, oil, grease, de-icing salts and abrasion.

FEATURES/BENEFITS

- Provides a totally clear membrane that will not yellow.
- Seals all concrete surfaces, providing a gloss appearance and easier clean up.
- Offers improved slip resistance
- Applies easily.
- May be used on all concrete surfaces, including stamped or stained concrete.
- Provides a clear, tough film, which improves abrasion and stain resistance.
- Offers improved resistance to rain, sun, freezing temperatures, most acids and industrial chemicals, oil, grease, de-icing salts, cleaning agents (except aromatic solvents), caustics, airborne soot, dust, and other pollutants.
- Seals and enhances the beauty of many concrete surfaces for years.
- Can be recoated after thorough surface cleaning to restore original beauty.

PACKAGING

3.79 Litre (1 Gal.) Units
18.93 Litre (5 Gal.) Pails

COVERAGE

7.37 - 14.73 m²/L (300 - 600 ft.²/gal.). Coverage is approximate and may vary depending on surface finish/texture, concrete condition, climatic conditions, etc. Always apply to a test area first to determine actual coverage rate before full-scale application.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within one year of date of manufacture.

SPECIFICATIONS

- Complies with Canada VOC Concentration Limits for Architectural Coatings Regulations

PACKAGING

3.78 Litre (1 U.S. Gallon) Containers
18.9 Litre (5 U.S. Gallon) Pails

APPLICATION

Mixing ... For optimum performance, gentle mixing or agitation is recommended. CAUTION: DO NOT MIX EXCESSIVELY.

Surface Preparation

Existing Concrete ... Concrete surface must be clean and dry with all chemical form agents, stains, oil, grease, dust and dirt removed prior to application.

New Stamped Concrete (At Least 72 Hours [Three Days] Old) ... Surface must be clean and free from all powdered release agent residue. CAUTION: If a liquid compound other than W. R. MEADOWS CS-309™ series or VOCOMP® series products have been used, do not apply DECK-O-GRIP W/B until all traces of the compound have been completely removed and the surface is clean and dry.

Continued over ...

W. R. MEADOWS® OF CANADA

70 Hannant Court, Milton, ON L9T 5C1
38 Rayborn Crescent, St. Albert, AB T8N 4B1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
St. Albert, AB
www.wrmeadows.com

For most recent data sheet, further LEED information, and SDS, visit www.deckoseal.com.

2018-03-29

Application Method ... MIX THOROUGHLY PRIOR TO USING. A typical commercial sprayer provides an easy, economical method of application.

DECK-O-GRIP W/B should be sprayed with a 1949 sprayer and 0.379 LPM (0.1 GPM) nozzle. Spray on in a fine, fog pattern, without spurts or dribbles, to form a thin, continuous film. AVOID PUDDLING in low areas. If puddles occur, brush or roll them out. For added protection and a greater sheen on concrete, two coats of DECK-O-GRIP W/B applied at right angles is recommended. Additional coats may be applied after the first coat has thoroughly dried.

Drying Time ... DECK-O-GRIP W/B dries quickly. Drying times may be extended depending on application rate, temperature, humidity, and project conditions. Restrict foot traffic for at least six hours. Twelve hours is preferred.

Clean Up ... While DECK-O-GRIP W/B is still wet, equipment may be cleaned with soap and water. Once dried, the material may be removed with a solvent, such as xylene or toluene.

PRECAUTIONS

KEEP FROM FREEZING. Do not dilute. Do not apply when air, material, and surface temperatures are expected to fall below 4° C within four hours of completed application. DO NOT MIX WATER-BASED COMPOUNDS WITH ANY COMPOUND CONTAINING SOLVENT.

DECK-O-GRIP W/B is designed for coloured concrete, but mottling may occur. Surfaces that have been acid-stained or acid-washed must be neutralized to a pH of seven. Do not use on dense or non-porous surfaces. For other specifications, secure the approval of the paint or resilient flooring manufacturer before applying product. Improper application of a sealer may prevent the film from adhering properly. Poor adhesion and/or entrapped moisture may cause the film to peel and/or turn white (blush). The specifier and user shall determine the suitability and assume all responsibilities therewith.

HEALTH AND SAFETY

Direct contact may result in mild irritation. Inhalation may cause irritation of the respiratory tract. Refer to Safety Data Sheet for complete health and safety information.

MASTERFORMAT NUMBER AND TITLE

03 05 00 - Common Work Results for Concrete

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.