



DATA SHEET NO. 3554-000

EXPO-GLOSS® OTC “Wet Look” Exposed Aggregate Sealer

DESCRIPTION

EXPO-GLOSS OTC exposed aggregate concrete sealer is a transparent, high solids, film-forming, curing, sealing, and dustproofing compound that improves resistance to staining and wear. EXPO-GLOSS OTC is specifically formulated to enhance the beauty of exposed aggregate concrete surfaces, while providing maximum surface protection. When properly applied, EXPO-GLOSS OTC produces a glossy “wet look” finish.

USES

EXPO-GLOSS OTC is ideal for freshly finished exposed aggregate concrete surfaces. It is also equally applicable for use on old exposed aggregate concrete surfaces.

NOTE: EXPO-GLOSS OTC should not be used on standard concrete, polymer-modified surfaces/overlays, or aggregate overlays. Please refer to PRECAUTIONS for additional substrate limitations.

FEATURES/BENEFITS

- Provides shiny, wet look ... enhances the beauty of natural stone in exposed aggregate concrete.
- Permeable film allows moisture in cured exposed aggregate substrates to evaporate.
- Available in transparent and Merrimac Brown formulations.
- Applies easily to freshly finished or old exposed aggregate concrete surfaces.
- Dries quickly once applied.
- Cure, seal, and dustproof with a single product.
- Improves resistance to staining and wear.
- Ready to use.

PACKAGING

3.79 Litre (1 Gal.) Cans, 18.9 Litre (5 Gal.) Pails, 208.20 Litre (55 U.S. Gal.) Drums

COVERAGE

Coverage is 7.37 - 14.73 m²/L (300 - 600 ft.²/gal.). Coverage is approximate and may vary depending on surface finish/texture, concrete condition, climatic conditions, etc. Always apply to a test area first to determine actual coverage rate before full-scale application.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

SPECIFICATIONS

- AASHTO M 148, Type 1, Classes A & B
- ASTM C309, Type 1, Classes A & B
- ASTM C1315, Type 1, Class A
- Complies with Canada VOC Concentration Limits for Architectural Coatings Regulations

APPLICATION

Surface Preparation

Fresh (New) Exposed Aggregate Concrete ... Apply EXPO-GLOSS OTC to freshly placed and finished exposed aggregate concrete surfaces once the aggregate exposure process is complete and all surface moisture has disappeared. Before applying EXPO-GLOSS OTC, make sure all cement paste residue has been thoroughly removed and there is no standing or puddled water on the surface.

Existing (Old) Exposed Aggregate Concrete ... The existing surface must be thoroughly clean and free of all stains, oil, grease, dust, dirt, curing compounds, etc. before applying EXPO-GLOSS OTC. The surface may be damp, but do not apply EXPO-GLOSS OTC to exposed aggregate concrete surfaces containing standing or puddled water.

Mixing ... For optimum performance, gentle mixing or agitation is recommended. **CAUTION: TO AVOID FOAMING, DO NOT MIX EXCESSIVELY.**

Application Method ... Apply using a good quality natural bristle brush or a short nap roller. Spread in a thin, even coat, being careful to avoid puddling.

Continued over ...

W. R. MEADOWS OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
21 Streambank Ave., Sherwood Park, AB T8H 1N1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
Sherwood Park, AB
www.wrmeadows.com

Drying ... Drying times may be extended depending on application rate, temperature, humidity, and project conditions. Protect the freshly coated surface from traffic, dust, condensation, and rain while drying. The surface will be slippery while drying and may become slippery once dry under certain conditions.

Cleanup ... Clean tools with an aromatic solvent immediately after finishing application.

PRECAUTIONS

FOR OUTSIDE/EXTERIOR APPLICATION ONLY. KEEP AWAY FROM ALL OPEN FLAMES, SPARKS, IGNITION SOURCES, etc. Use with adequate ventilation and block all HVAC ventilation ducts which may spread product vapours - vapours are flammable and heavier than air. If product odors are objectionable, W. R. MEADOWS recommends using a water-based product, such as DECRA-SEAL™ W/B or any of the VOCOMP® series products. EXPO-GLOSS OTC must be applied without diluting or thinning. Surfaces treated with EXPO-GLOSS OTC may become slippery under certain conditions. To increase slip resistance, addition of SURE-STEP™ from W. R. MEADOWS is recommended.

EXPO-GLOSS OTC is specifically designed for exposed aggregate concrete surfaces only. Do not use EXPO-GLOSS OTC on standard concrete. Do not use on polymer-modified surfaces or aggregate overlays, including topping, overlays, concrete overlays, mortars, resin/aggregate coatings/systems, decorative toppings, terrazzo surfaces, etc. Do not use on extremely porous substrates, such as brick, or on dense/non-porous surfaces, such as stone.

EXPO-GLOSS OTC should not be applied on hot exposed aggregate concrete surfaces in direct sunlight or during high temperature conditions. These conditions cause rapid evaporation of EXPO-GLOSS OTC, preventing proper film formation. Under these conditions, the EXPO-GLOSS OTC film may peel, become hazy, bubble, turn white (blush), and/or not adhere properly to the exposed aggregate surface. Apply EXPO-GLOSS OTC when the surface temperature of the exposed aggregate concrete and air temperature are between 4° - 32° C.

EXPO-GLOSS OTC should not be applied to exposed aggregate concrete substrates subjected to excessive moisture. This excessive moisture can become trapped in the EXPO-GLOSS OTC film and cause it to peel, turn white (blush), and/or not adhere properly to the exposed aggregate concrete surface.

Do not over-apply EXPO-GLOSS OTC. Over-application may cause the film to discolor, peel, become hazy, turn white (blush), become hazy and/or not adhere properly to the exposed aggregate concrete surface.

HEALTH AND SAFETY

EXPO-GLOSS OTC IS FLAMMABLE. Remove ignition sources prior to use. Empty containers may contain FLAMMABLE vapours. Handle empty containers as FLAMMABLE liquids.

Direct contact with the product or exposure to product vapours may cause irritation of the eyes and/or skin. Inhalation of vapours in excess of permissible exposure limits may result in symptoms of transient central nervous system depression.

In the event of a spill, contain the product, apply absorbents and place in sealed containers. In the event of a fire, contain all run-off water. Refer to product Safety Data Sheet for complete health and safety information.

MASTERFORMAT NUMBER AND TITLE

03 35 23 - Exposed Aggregate Concrete Finishing

2021-12-16



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.