



DATA SHEET NO. 5125-000

WATERSTOP EC PLUS

DESCRIPTION

WATERSTOP EC PLUS is comprised of a sodium bentonite/hydrophilic rubber combination designed to provide a superior watertight seal while at the same time offering the ability to work in an environment subjected to continuous wetting and drying cycles. Full hydration and/or dehydration takes approximately four days.

USES

WATERSTOP EC PLUS is used to seal static construction joints in concrete footings, walls, floors, tunnels, and parking and plaza decks and to prevent water migration. WATERSTOP EC PLUS has superior performance when used under conditions of extreme water head. WATERSTOP EC PLUS is compatible with all waterproofing membranes available from W. R. MEADOWS.

FEATURES/BENEFITS

- When properly applied, stops water migration through cast-in-place concrete construction joints after confinement.
- Returns to original placement and size after one prolonged hydration cycle.
- Resistant to a variety of chemical contaminants common to urban water and soil samples.

PACKAGING

Standard rolls sizes:

12.7 mm x 25.4 mm x 5.1 m (1/2" x 1" x 16' 8")

19.1 mm x 25.4 mm x 5.1 m (3/4" x 1" x 16' 8")

Each carton provides 30.5 lm (100 LF) of coverage. Rolls are packaged six per carton. Protect product from moisture in storage. Store on skid or pallet. Cover with polyethylene or tarp.

APPLICATION

Surface Preparation ... Surface should be clean and dry. For optimum adhesion to concrete, use CLAY-TITE MASTIC from W. R. MEADOWS. Place bead of material across surface before installation of WATERSTOP EC PLUS. Concrete should cover 50 mm (2") surrounding the WATERSTOP EC PLUS application area.

Application Method ... After applying CLAY-TITE MASTIC, remove the thin liner and press the product into place. The product should be applied with the nylon side up. After WATERSTOP EC PLUS is hand-pressed into place, then install standard masonry nails. The nails should be placed 304.8 mm (12") apart. After the nails are placed, release the thick liner. Then concrete can be poured or placed.

PRECAUTIONS

Do not install in standing water or over ice. WATERSTOP EC PLUS is not designed, nor intended to function, as an expansion joint sealant. WATERSTOP EC PLUS is designed to seal structural concrete joints with a minimum 20.7 MPa (3000 psi) compressive concrete strength. If WATERSTOP EC PLUS has eclipsed 24 hours of continuous submersion, allow an appropriate or equal time to dry before placement of concrete or replace with new product. CLAY-TITE MASTIC may be applied over damp surfaces, but must not be applied over dust, debris or standing water as proper adhesion will not take place

MASTERFORMAT NUMBER AND TITLE

03 15 13 - Concrete Accessories - Waterstops

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management

For most current data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

Continued over ...

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
21 Streambank Ave., Sherwood Park, AB T8H 1N1
(800) 342-5976
Montreal Sales: (514) 865-2406

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
Sherwood Park, AB
www.wrmeadows.com
info@wrmeadows.com

Property	Test Method	WATERSTOP EC PLUS Results
Colour		Black
Weight		0.4 kg/m (0.25 lb./linear foot)
Tear Strength: Membrane	ASTM D1004	333 N (75 lb.)
% Elongation at Break	ASTM D638	>150%
Unrestricted Expansion		300% over 4 days
Installation Temperatures	ASTM D746	-26° to 49° C
Freeze/Thaw Cycles		No effect before or after installation.
Resistance to Hydrostatic Head	ASTM D5385	70 m (231') of water
Vapor Permeability	ASTM D5084	1 x 10 ⁻⁹ cm per sec

2019-06-19



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.