



DATA SHEET NO. 6035-000

AIR-SHIELD™ LIQUID FLASHING Liquid Flashing Membrane

DESCRIPTION

AIR-SHIELD LIQUID FLASHING is a high-quality, gun grade, low-odour, elastomeric, polyether, liquid-applied flashing and detailing membrane. It bonds to most construction materials, such as aluminum, brick, concrete, wood, and vinyl and exterior gypsum board.

USES

AIR-SHIELD LIQUID FLASHING is to be used as a liquid-applied flashing, compatible with the entire line of AIR-SHIELD air, vapour, and liquid moisture barriers from W. R. MEADOWS. This general-purpose, wet flashing membrane is used to seal rough openings and detail joints between exterior gypsum board. AIR-SHIELD LIQUID FLASHING is designed for window and door flashing applications. The product will not harm foam insulation.

FEATURES/BENEFITS

- Can be applied in damp conditions.
- Does not peel back when left exposed.
- Does not create buildup in rough openings.
- Non-sag.
- 100% solvent free.
- Non-shrinking.
- Bonds to most construction materials.
- Paintable in 24 hours.
- Guns and tools easily.
- Does not harm foam insulation.

PACKAGING

600 mL (20 Oz) Sausages (12/Carton)
13.2 L (3.5 Gal.) Units

COVERAGE

600 mL (20 Oz.) Sausage
12 – 15 Mils 1.4 – 1.8 m² (15 – 19 ft.²)
Coverage rates will vary depending on the surface the material is applied on.

SHELF LIFE

When stored indoors and in original, unopened containers between 4° - 32° C, shelf life is one year from date of manufacture.

SPECIFICATIONS

- Complies with VOC Concentration Limits for Architectural Coatings Regulations in Canada

TECHNICAL DATA

Chemistry	Silyl-Terminated Polyether – Moisture Cure	
Tack Free Time	30 min +/- 15 min	ASTM C679
Shear Strength	210 psi +/- 25 psi	ASTM D412
Low Temperature Flex	Pass @ -23° C	ASTM D816
Installation Temperature	>0° C	
Service Temperature	-29° to 93° C	
Shrinkage	No Visible Shrinkage After 14 Days	
Exposure Time	12 Months	
Colour	Green	

APPLICATION

Surface Preparation ... All surfaces to receive AIR-SHIELD LIQUID FLASHING should be clean, smooth, and free from all bond-breaking contaminants. Product can be applied to damp surfaces if it is clean. Remove any damaged structural wall components. Any raw edges of exterior gypsum board may require adhesive. For detailed instructions, view the AIR-SHIELD LIQUID FLASHING INSTALLATION GUIDELINES document at www.wrmeadows.com.

Continued over ...

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
21 Streambank Ave., Sherwood Park, AB T8H 1N1
(800) 342-5976
Montreal Sales: (514) 865-2406

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
Sherwood Park, AB
www.wrmeadows.com
info@wrmeadows.com

Application Method

Rough Opening ... Inspect rough opening. The rough or cut edge of gypsum board should be applied with adhesive. Prefill any gaps with larger than 6.35 mm (¼") with AIR-SHIELD LIQUID FLASHING and allow to skin over.

Apply bead of AIR-SHIELD LIQUID FLASHING in opening to be sealed. Spread the material using putty knife across rough opening surface. Next, apply a thick bead of material to the structural wall surface around rough opening. Again, spread the material evenly using a putty knife. Make sure material is spread in an even, monolithic manner. Make sure to spread the material 12 – 15 mils (100 – 152 mm) on to structural wall. Make sure material contains no pinholes and is void-free. Again, make sure material is even, monolithic, and undamaged.

Make sure AIR-SHIELD LIQUID FLASHING covers the entire opening and seamlessly joins the specific AIR-SHIELD membrane being installed. Allow surface to dry before installing windows, doors, wall assembly, and specific AIR-SHIELD membrane being applied.

AIR-SHIELD LIQUID FLASHING is also compatible with the entire line of AIR-SHIELD products for joint detailing in exterior sheathing panels. For detailed application instructions, please view the AIR-SHIELD EXTERIOR SHEATHING PANELS INSTALLATION GUIDELINES document at www.wrmeadows.com.

Drying Time ... At 21° C and 50% relative humidity, product skins within 30 minutes. AIR-SHIELD LIQUID FLASHING is moisture curing. Low temperatures and low relative humidity slow dry time. High temperatures and high relative humidity accelerates dry time.

PRECAUTIONS

Not for use as a structural sealant. Not for use in place of AIR-SHIELD THRU-WALL FLASHING from W. R. MEADOWS. Not for use below-grade or in locations designed to be continuously immersed in water. When painting, use latex paints only. Adhesion of membrane on oriented strand board (OSB) can sometimes be affected by the level of surface texture or the presence of wax that is part of the binder used to bond together the wood strands. Adhesion of membrane to fire treated wood can sometimes be adversely affected by the treatment. Prior to placement on OSB or treated wood, in-situ adhesion tests should be performed to determine suitability of substrate prior to full installation. If there are variations in the OSB or fire-treated wood surface, multiple tests may be required.

MASTERFORMAT NUMBER AND TITLE CLAUSE

07 27 26 – Fluid-Applied Membrane Air Barriers

For most current data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

2021-10-16



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.