



DATA SHEET NO. 6062-000

REINFORCING FABRIC HCR Reinforcement Material

DESCRIPTION

REINFORCING FABRIC HCR is a spun-bonded polyester hot/cold reinforcing fabric.

USES

REINFORCING FABRIC HCR is designed to be used as a standard reinforcement material for the W. R. MEADOWS line of building envelope products, including HRM 714 and HYDRALASTIC 836. It is used to reinforce the various membranes over cracks, construction joints, and changes-in-plane. The product can also be used with the AIR-SHIELD™ line of air barriers from W. R. MEADOWS for taping of joints for optimum performance. REINFORCING FABRIC HCR can also be used in door and window flashings.

PACKAGING

Rolls of:

76 mm x 183 m (3" x 600') 229 mm x 183 m (9" x 600') 300 mm x 183 m (12" x 600') 991 mm x 183 m (39" x 600')

TECHNICAL DATA

Property	Test Method	Result
Color		White
Unit Weight (g/m²)	ASTM D1910	45.77
% Elongation (To Break)	ASTM D2523	42
Tear Strength (kg)	ASTM D2263	3.63
Breaking Strength (kg)	ASTM D2523	11.34

MASTERFORMAT NUMBER AND TITLE

07 00 00 – Thermal and Moisture Protection

LEED INFORMATION

May help contribute to LEED credits:

- MR Credit 2: Construction Waste Management
- MR Credit 4: Recycled Content
- MR Credit 5: Regional Materials

For further LEED information and MSDS, visit www.wrmeadows.com.

2013-06-28



W. R. MEADOWS OF CANADA

70 Hannant Court, Milton, ON L9T 5C1 Phone: (905) 878-4122 • Fax: (905) 878-4125

Montreal Sales: (877) 405-5186

Hampshire, IL/Cartersville, GA/York, PA/Fort Worth, TX Benicia, CA/Pomona, CA/Goodyear, AZ/Milton, ON St. Albert, AB

www.wrmeadows.com