



DATA SHEET NO. 7100-452

DETAIL STRIP

DESCRIPTION

DETAIL STRIP is a rugged, 65 mil thick, self-adhering elastomeric tape. The tape provides a simple, easy, and economical method of effectively sealing horizontal and vertical joints. The product may be used as an installation option with hot-applied systems when approved by the manufacturer, as well as PROTECTION COURSE, MEL-ROL®, AIR-SHIELD™, MEL-DRAIN®, and MEL-DEK® from W. R. MEADOWS.

USES

DETAIL STRIP is routinely used to seal construction joints and changes of plane in waterproofing. Other applications include sealing random cracks and open joints in concrete pipe or culverts and in conjunction with hot-rubber membranes. The tape is produced with a quick release, anti-stick paper for ease of handling and application. DETAIL STRIP can be used on inside and outside corners and between wall and footings prior to application of the waterproofing membrane.

FEATURES/BENEFITS

- Controlled thickness membrane is ideal for transition membrane applications.
- Woven polypropylene carrier sheet provides excellent tensile strength, elongation, and tear-resistance.
- Membrane maintains flexibility at low temperatures.
- Rugged membrane can actually fold to shape during application for ease of application in inside and outside corners.
- Excellent adhesion to prepared substrates of precast concrete, cast-in-place concrete, masonry (concrete block), interior and exterior gypsum board, Styrofoam, primed steel, aluminum mill finish, anodized aluminum, primed galvanized metal, drywall, and plywood.
- Self-healing characteristics facilitate recovery if minimal damage is sustained under normal use applications.

PACKAGING

228.6 mm x 15.2 m (9' x 50') Rolls

TECHNICAL DATA

Thickness	65 mils
Tensile, ASTM D-1682	
Warp, lb.	68.0 kg (150 lbs)/20%
Film, lb.	40.8 kg (90 lbs)/15%
Puncture, ASTM D-751	0.34 MPa (50 psi)
Burst, ASTM D-751	2.41 MPa (350 psi)
Pliability, ASTM D-146	
180 bond, 25 mm (1") mandrel @ -31° C	No cracks in fabric or polymeric

These typical properties should not be considered for establishing minimum physical properties.

APPLICATION

Surface Preparation ... Concrete should be cured at least 72 hours, be clean, dry, smooth, and free of voids. Repair spalled areas; fill all voids and remove all sharp protrusions. A clear, resin-based concrete curing compound that contains no wax, oil, pigments, or silicones may be used. Use a form release that will not transfer to the concrete.

Surface Conditioning ... Apply MEL-PRIME™ or MEL-PRIME W/B from W. R. MEADOWS or approved alternate to all concrete surfaces using a roller, brush, or sprayer. Condition only the area to be covered that day; uncovered areas must be reconditioned the next day.

Temperature ... DETAIL STRIP can be applied at temperatures of -4° C or higher.

Footing Details ... Fold DETAIL STRIP lengthwise and then cut at fold. Next, coat the keyway with BEM from W. R. MEADOWS. Pour the walls. Install DETAIL STRIP horizontally along the wall where it meets the footing, placing half the material up the wall and the other half onto the footing. Extend the material 114.3 mm (4.5") beyond outside corners. Slit extended portion of DETAIL STRIP lengthwise. Place the horizontal flap out onto the footing and bend the vertical flap around the wall. Repeat this procedure in the opposite direction.

Inside Corners ... Place a vertical DETAIL STRIP on inside corners, extending the material 114.3 mm (4.5") beyond each side of the corner. Terminate at the footing and finish the corner with POINTING MASTIC from W. R. MEADOWS.

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
38 Rayborn Crescent, St. Albert, AB T8N 4B1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
St. Albert, AB
www.wrmeadows.com

Outside Corners ... Bend a DETAIL STRIP vertically over the outside corner and extend 114.3 mm (4.5") beyond each side of the corner. Terminate the material at the footing. Finish the corner with POINTING MASTIC from W. R. MEADOWS.

MASTERFORMAT NUMBER AND TITLE
07 13 53 – Elastomeric Sheet Waterproofing

LEED INFORMATION

May help contribute to LEED credits:

- IEQ Credit 3.1: Construction Indoor Air Quality Management Plan: During Construction
- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

For further LEED information and SDS, visit www.wrmedows.com.

2016-04-22



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.