



W. R. MEADOWS

SEALTIGHT

DATA SHEET NO. 7100-600

600 Asphalt Primer

DESCRIPTION

600 Asphalt Primer is a unfilled, cutback asphalt for priming surfaces prior to the application of waterproofing or roof coatings. It has excellent penetration properties.

USE

600 Asphalt Primer is designed for priming surfaces to improve the bond of hot or cold applied asphalt coatings. For use on wood, concrete, asphalt, masonry and steel.

LIMITATIONS

Although 600 Asphalt Primer is designed to increase the bond of asphalt coatings to various substrates, it does not replace the need for proper surface preparation.

PACKAGING

18.9 Litre Pails

Standards

Complies with CGSB 37-GP-9Ma. To be applied according to CGSB 37-GP-15M.

Working Characteristics

Particularly suited for use on old built-up roofs prior to the application of new roofing materials. Coverage from 150 ft²/gal (3.1 m²/L) to 200 ft²/gal (4.1 m²/L) depending on surface porosity.

PHYSICAL PROPERTIES

Color	Black
Solids	32%
Weight	9 lbs/gal (.91 kg/L)
Drying Time	Touch dry 1 hour Firm dry 12 hours
Application Temperature	-4oF (-20oC) Minimum
Flammability	Wet Flammable Dry Burns
Water Content	1% Maximum
Flash Point	104oF (40oC)

APPLICATION

Preparatory Work

Surface shall be firm and free from loose particles, cracks, grease, oil and other foreign matter. Surface must be free from frost, snow and ice.

Installation Instructions

- Apply by brush or sprayer at a minimum rate of 250 ft²/gal (5.2 m²/L).
- Take care that the primer is dry before the application of subsequent coats of asphalt materials.
- Use mineral spirits for cleanup.

Safety Precautions

Contains flammable solvents. Keep away from heat and open flames. Use in a well-ventilated area. Avoid use where solvent odors may be objectionable.

W. R. MEADOWS OF WESTERN CANADA
38 Rayborn Crescent, St. Albert, AB T8N 5B4
Phone: (780) 458-8773 • Fax: (780) 458-1173

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
St. Albert, AB
www.wrmeadows.com



2005-01-07

© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.