



## PMPC TAPE

### Membrane Tape for Overlap Seams

#### DESCRIPTION

PMPC TAPE is a self-adhesive tape used in conjunction with the application of PREMOULDED MEMBRANE® VAPOR SEAL WITH PLASMATIC® CORE (PMPC). PMPC TAPE provides the same water permeance properties (0.0011 perms) as PMPC, which is the lowest in the industry.

#### USES

PMPC TAPE is designed for sealing PMPC membrane seams and for attachment to footings, protrusions, etc.

#### FEATURES/BENEFITS

- Backing stabilized to resist the effects of UV exposure.
- Product is very conformable.
- Maintains a watertight seal in all weather conditions.

#### PACKAGING

PMPC TAPE is offered in 152.4 mm (6") widths and roll lengths of 15 m (50'), six rolls per carton.

#### COVERAGE

One box of tape will adhere approximately 24 sheets of PMPC.

#### APPLICATION

**Surface Preparation ...** The PMPC TAPE area of adhesion should be free from dust, dirt, and moisture to allow maximum adhesion of the pressure-sensitive tape. The anti-stick on PMPC should be removed prior to applying PMPC TAPE.

**Sealing Seams/Attaching to Footing ...** All lateral joints/seams in the membrane application can be overlapped and taped or butt-jointed and taped using 152.4 mm (6") wide PMPC TAPE. The most efficient installation method includes placing PMPC on top of the footing and against the vertical wall. This will sandwich PMPC between the footing, vertical wall, and poured concrete floor. This will help protect the concrete slab from external moisture sources once the slab has been placed.

DATA SHEET NO. 7100-711A

**Sealing Protrusions ...** Cut a slit around pipes, ductwork, rebar, and wire penetrations to place the initial layer of the membrane. To further protect the concrete slab from external moisture sources, use a piece of PMPC and place a collar around these as well.

1. Cut a piece of PMPC a minimum of 304.8 mm (12"). The length should be 1 1/2 times the pipe circumference. With a roofer's knife or scissors, cut "fingers" half the width of the film.
2. Wrap around and tape the collar onto the pipe and completely tape fingers to the bottom layer of PMPC.

In the event that PMPC is damaged during or after installation, repairs must be made. Cut a piece of the membrane large enough to cover any damage by a minimum overlap of 152.4 mm (6") in all directions. Clean all adhesion areas of dust, dirt, and moisture. Tape down all edges using PMPC TAPE.

#### MASTERFORMAT NUMBER AND TITLE

07 26 16 - Below-Grade Vapour Retarders

#### LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management
- EAp2: Minimum Energy Performance
- EAc2: Optimize Energy Performance

For most current data sheet, further LEED information, and SDS, visit [www.wrmeadows.com](http://www.wrmeadows.com).

2018-05-08



**W. R. MEADOWS OF CANADA**  
70 Hannant Court, Milton, ON L9T 5C1  
21 Streambank Ave., Sherwood Park, AB T8H 1N1  
(800) 342-5976  
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX  
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /  
Sherwood Park, AB  
[www.wrmeadows.com](http://www.wrmeadows.com)

© SEALTIGHT is a registered trade mark of W. R. Meadows

**WARRANTY:** W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.