

# PRODUCT DATA

NO. 718-D

MasterFormat:  
04 05 23  
07 65 26

W. R. MEADOWS®

SEALTIGHT®

JUNE 2016  
(Supersedes November 2011)

## AIR-SHIELD™ 25 MIL FLASHING TAPE

Flexible Flashing, 25 Mils Thick

### DESCRIPTION

AIR-SHIELD 25 MIL FLASHING TAPE is a self-adhering, flexible membrane flashing. It is a roll-type product that is nominally 25 mils thick. This material is an air, vapor, and liquid moisture barrier. When properly applied, the product reduces the risk of rot and mold development.

### USES

AIR-SHIELD 25 MIL FLASHING TAPE provides protection against water infiltration in critical detail areas, such as window and door openings, deck-to-wall intersections, corner boards, wall-to-wall tie-ins, foundation sill plates, sheathing panel seams, under stucco finishes, masonry walls, and other non-roof detail areas.

### FEATURES/BENEFITS

- Easy to install.
- Reduces the risk of rot and mold development.
- Superior adhesion.
- Seals around fasteners.
- Watertight.

### PACKAGING

Available in cut sizes. Also available in cut rolls of 4", 6", 9", and 12" (102, 152, 224, 326 mm) wide. NOTE: Some sizes require lead time. All rolls are 75' (22.9 m) long.

### TECHNICAL DATA

**Thickness** 25 mils

### APPLICATION

**Surface Preparation ...** Apply AIR-SHIELD 25 MIL FLASHING TAPE in fair weather conditions when the air, surface and membrane are at temperatures of 25° F (-4° C) or higher. After precipitation, allow a minimum of 24 hours for drying before installation. Install directly onto a clean and dry surface. Remove dust, dirt, and loose nails. Protrusions must be removed. Surfaces should have no voids or damaged/unsupported areas. Repair surfaces before installing. Surfaces should be free of scale, rust, grease, and oil and conditioned with MEL-PRIME™ or MEL-PRIME W/B from W. R. MEADOWS.

**Application Method ...** Cut AIR-SHIELD 25 MIL FLASHING TAPE to desired length. Peel back the release paper to expose adhesive. Align the membrane and press into place with heavy hand pressure. Laps must be a minimum of 3" (75 mm). Consistent with good construction practice, install the membrane so that all laps shed water (following the shingle principle). The top membrane layer should go over the bottom layer. Always work from low point to high point.

### PRECAUTIONS

Do not leave the product permanently exposed to sunlight. Maximum recommended exposure time is 30 days.

*CONTINUED ON REVERSE SIDE...*

### **LEED INFORMATION**

May help contribute to LEED credits:

- EA Credit 1: Optimize Energy Performance
- IEQ Credit 3.1: Construction Indoor Air Quality Management Plan – During Construction
- IEQ Credit 7.1: Thermal Comfort – Design
- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

**For further LEED information and SDS, visit [www.wrmeadows.com](http://www.wrmeadows.com).**



### **LIMITED WARRANTY**

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

### **Disclaimer**

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.