

DATA SHEET NO. 7260-723A

PERMINATOR® TAPE
Overlap Seam Tape

DESCRIPTION

PERMINATOR TAPE is a self-adhesive tape, used in conjunction with the application of PERMINATOR underslab vapour barrier.

USES

PERMINATOR TAPE is for use in sealing vapour barrier seams and attachment to footings, protrusions, etc.

FEATURES/BENEFITS

- Backing stabilized to resist the effects of UV exposure.
- Product is very conformable.
- Maintains a watertight seal in all weather conditions.

PACKAGING

PERMINATOR TAPE is offered in 10 cm (4") widths and roll lengths of 55 m/roll (180') (12 Rolls/Carton).

COVERAGE

One box of tape will adhere approximately 10 rolls of PERMINATOR.


TECHNICAL DATA

Thickness: 8 Mils (0.2 mm)

APPLICATION


Surface Preparation . . . The PERMINATOR TAPE area of adhesion should be free from dust, dirt, and moisture, to allow maximum adhesion of the pressure-sensitive tape.

Sealing Seams/Attaching to Footing . . . All joints/seams in the vapour barrier application, both lateral and butt, should be overlapped 152.4 mm (6") and taped using PERMINATOR TAPE. The most efficient installation method includes placing PERMINATOR on top of the footing and against the vertical wall. This will sandwich PERMINATOR between the footing, vertical wall, and poured concrete floor. This will help protect the concrete slab from external moisture sources once the slab has been placed.



Sealing Protrusions . . . Cut a slit around pipes, ductwork, rebar and wire penetrations to place the initial layer of the vapour barrier. To further protect the concrete slab from external moisture sources, use a piece of vapour barrier and place a collar around these as well.


1. Cut a piece of PERMINATOR a minimum of 304.8 mm (12"). The length should be 1 1/2 times the pipe circumference. With a roofer's knife or scissors, cut "fingers" half the width of the film.



2. Wrap around and tape the collar onto the pipe and completely tape fingers to the bottom layer of PERMINATOR.

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
38 Rayborn Crescent, St. Albert, AB T8N 4B1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
St. Albert, AB
www.wrmeadows.com



In the event that PERMINATOR is damaged during or after installation, repairs must be made. Cut a piece of the vapour barrier large enough to cover any damage by a minimum overlap of 152.4 mm (6") in all directions. Clean all adhesion areas of dust, dirt and moisture. Tape down all edges using PERMINATOR TAPE.

MASTERFORMAT NUMBER AND TITLE

07 26 16 - Below-Grade Vapor Retarders

LEED INFORMATION

May help contribute to LEED credits:

- EA Credit 1: Optimize Energy Performance
- IEQ Credit 3.1: Construction Indoor Air Quality Management Plan - During Construction
- IEQ Credit 7.1: Thermal Comfort - Design
- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials
- SS Credit 3: Brownfield Redevelopment

For most current data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

2016-11-08



© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.