



MasterFormat: 07 17 16

SEPTEMBER 2017

## CLAY-TITE™ GRANULAR PACK

### Bentonite Clay Detail Material

#### DESCRIPTION

CLAY-TITE GRANULAR PACK is a package of bentonite clay granules that is used as a detail material in conjunction with the CLAY-TITE line of waterproofing products.

#### USES

CLAY-TITE GRANULAR PACK is designed for waterproofing below-grade structural slabs as well as construction methods incorporating lagging, concrete caisson, or shotcrete retention walls. Applications include foundation wall bases, vertical-to-horizontal transitions, penetrations detailing, void filling, and horizontal application seams.

#### FEATURES/BENEFITS

- Details penetrations.
- Fills voids.
- Ensures a complete, seamless CLAY-TITE waterproofing installation.

#### PACKAGING

30 Lb. (13.6 Kg) Bags

#### COVERAGE

One 30 lb. (13.6 kg) pack covers approximately 25 - 30 linear feet (82 - 98.4 m)

#### SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 40° - 90° F (4° - 32° C), optimum performance and best use is obtained within two years of date of manufacture.

#### TECHNICAL DATA

Screen Analysis	Typical
Dry Screen, 16 mesh	100%
Dry Screen, 10 mesh	1.7%
Wet Screen 200 mesh	1.3%
AFS Grain Fineness	25
<b>Industrial Properties</b>	

Moisture	8.2%
Viscosity @ 600 RPM	25
Filtrate, 30 minutes @ 100 psi (0.689 MPa)	18
Montmorillonite	92%

#### APPLICATION

**Application Method** ... Lay CLAY-TITE GRANULAR PACK on its side. Cut a 1" (152.4 mm) opening in the lower corner. Dispense a 1.5" - 2" (38 - 50 mm) can't along all vertical-to-horizontal transitions or on horizontal seams. After installation, no further maintenance is needed. For further information for application of CLAY-TITE GRANULAR PACK with CLAY-TITE in backfilled walls, blindside, and underslab installations, please visit [www.wrmeadows.com](http://www.wrmeadows.com) and refer to the available INSTALLATION GUIDELINES documents.

#### LEED INFORMATION

May help contribute to LEED credits:

- EAp2: Minimum Energy Performance
- EAc2: Optimize Energy Performance
- MRc9: Construction and Demolition Waste Management

**For further LEED information and SDS, visit**

[www.wrmeadows.com](http://www.wrmeadows.com).

**CONTINUED ON THE REVERSE SIDE...**

#### W. R. MEADOWS, INC.

P.O. Box 338 • HAMPSHIRE, IL 60140-0338  
 Phone: 847/214-2100 • Fax: 847/683-4544  
 1-800-342-5976  
[www.wrmeadows.com](http://www.wrmeadows.com) • [info@wrmeadows.com](mailto:info@wrmeadows.com)

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA  
 FORT WORTH, TX / BENICIA, CA / POMONA, CA  
 GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB



**LIMITED WARRANTY**

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

**Disclaimer**

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.