

PRODUCT DATA

W. R. MEADOWS®

SEA^TLIGHT®

MasterFormat: 03 15 13

NO. 732-A

WATERSTOP EC

JUNE 2017

DESCRIPTION

WATERSTOP EC is a multilayered, bentonite-based waterstop for construction joints. The self-sealing properties of bentonite are encased within a hydration-resistant core providing both extreme free swell properties as well as delayed swell properties. The multilayered structure with polypropylene fabric and strong tear-resistant netting provides for additional strength and structure. WATERSTOP EC will provide superior performance over the life expectancy of the structure.

USES

WATERSTOP EC is used to seal non-moving construction joints in concrete footings, walls, floors, tunnels, and parking and plaza decks and to prevent water migration. The product can also be used around pipes and other types of penetrations. WATERSTOP EC has superior performance when used under conditions of extreme water head.

FEATURES/BENEFITS

- Provides both extreme free swell properties as well as delayed swell properties.
- Provides additional strength and structure.
- Provides superior performance over the life expectancy of the structure.
- High expansion properties seals open areas in concrete surface.

PACKAGING

Standard rolls sizes:

1/2" x 1" x 15' (12.7 mm x 25.4 mm x 4.6 m)

3/4" x 1" x 15' (19.1 mm x 25.4 mm x 4.6 m)

STORAGE AND HANDLING

Protect from moisture. Store on skid or pallet. Cover with polyethylene or tarp.

APPLICATION

Surface Preparation ... Ensure that surface is free from protrusions and debris. If there are voids in the surface, fill with CLAY-TITE™ MASTIC from W. R. MEADOWS prior to installation of waterstop.

Application Method ... WATERSTOP EC is designed for use on vertical and horizontal construction joints with a minimum of 2" (50.8 mm) of containment. CLAY-TITE MASTIC will fill voids in rough concrete and provide additional adhesion to the concrete while preventing water or concrete from seeping under WATERSTOP EC. If surface is troweled smooth, lay a 1/8" - 1/4" (3.2 - 6.4 mm) bead of CLAY-TITE MASTIC along the joint. Surfaces to receive the waterstop cannot have protrusions greater than 1/2" (12.7 mm). Press WATERSTOP EC into uncured CLAY-TITE MASTIC and nail every 15" (381 mm) on center. Attach WATERSTOP EC with a washer nail [1" (25.44 mm) shank] with washer [5/8" -13/16" (15 - 23 mm)]. Butt ends for a continuous application.

PRECAUTIONS

Keep WATERSTOP EC dry; protect from exposure to the elements. WATERSTOP EC should be installed at least 2" (50.8 mm) from the face of the concrete. In areas of high salt concentration, a water sample may be required to determine site suitability for installation.

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management

For most current data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

CONTINUED ON REVERSE SIDE...

W. R. MEADOWS, INC.

P.O. Box 338 • HAMPSHIRE, IL 60140-0338
Phone: 847/214-2100 • Fax: 847/683-4544

1-800-342-5976
www.wrmeadows.com

HAMPSHIRE, IL /CARTERSVILLE, GA /YORK, PA
FORT WORTH, TX /BENICIA, CA /POMONA, CA
GOODYEAR, AZ / MILTON, ON /ST. ALBERT, AB

Property	Test Method	WATERSTOP EC Results
Weight		0.25 lb./linear foot (0.4 kg/m)
Tear Strength: Membrane	ASTM D1004	1/2": 75 lb. (333 N) 3/4": 112 lb. (500 N)
% Elongation at Break	ASTM D638	>150%
Unrestricted Expansion		300% over 4 days
Installation Temperatures	ASTM D746	-15° to 120° F (-25° to 50° C)
Freeze/Thaw Cycles		No effect before or after installation.
Resistance to Hydrostatic Head	ASTM D751, Procedure A	100' (30 m) of water
Vapor Permeability	ASTM D5084	1 x 10 ⁻⁹ cm per sec



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.