



MasterFormat: 07 13 00

NO. 737

OCTOBER 2021

DETAIL TAPE H

Polymeric Waterproofing Membrane

DESCRIPTION

DETAIL TAPE H is a polymeric waterproofing membrane on a shrink-resistant, heavy-duty, polypropylene woven carrier sheet. It is nominally 65 mils thick and is nominally 12" wide.

USES

DETAIL TAPE H can be used as a detailing option with PRECON® from W. R. MEADOWS in horizontal applications.

FEATURES/BENEFITS

- Self-adhesive
- Easy to apply with removable release paper
- Provides a secure, durable bond
- Compatible with PRECON

PACKAGING

12"(nominal) x 50' (304.8 mm x 15.24 m) Rolls, 4/Carton.

APPLICATION

Subgrade Preparation ... Ensure subgrade is smooth and compacted to help avoid the formation of creases (fish mouths) between the PRECON and DETAIL TAPE H during detailing tie-in procedure.

Application Method ... Place a strip of 12" (304.8 mm) DETAIL TAPE H with the adhesive side of the tape facing upwards. Remove the release paper on the one side of the tape, exposing 6" (152.4 mm) of the rubberized asphalt and apply the PLASMATIC® CORE side of the PRECON into this and roll press into place. Following this, remove the remaining release paper on the tape and apply the subsequent roll of PRECON into this area, making sure that both rolls are butted together. Roll press this into place. Following that, apply a 12" (304.8 mm) band of the POINTING MASTIC onto this overlap at a thickness of approximately 60 mils, and embed the DETAIL FABRIC into this. Please reference the END LAP TAPING METHOD TECHNICAL BULLETIN at www.wrmeadows.com for detailed visual installation instructions.

PRECAUTIONS

During the entire application process, ensure that DETAIL TAPE H remains clean, free of any containments, dirt, dust, sand, etc. that will interfere with creating a watertight bond between DETAIL TAPE H and PRECON.

DETAIL TAPE H is not compatible with most polyurethanes membranes or sealants.

For SDS, visit www.wrmeadows.com.

CONTINUED ON REVERSE SIDE ...



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.