

PRODUCT DATA



MasterFormat: 07 19 00

No. 795-A

NOVEMBER 2016
(Supersedes February 2010)

DECK-O-SHIELD™ PLUS

Natural Stone and Salt Water Resistant Sealer

DESCRIPTION

DECK-O-SHIELD PLUS is a premium-grade, ready-to-use, water-based sealer formulated for use on natural stone. DECK-O-SHIELD PLUS is formulated specifically to seal porous surfaces and is ideal to use on pool copings and decks protecting them from salt penetration. It can be used on all porous surfaces such as natural stone, concrete, pavers, and grout. DECK-O-SHIELD PLUS provides a solution to spalling and pitting of porous stone and concrete surfaces caused by salt penetration as well as surface damage caused by freeze-thaw cycles.

USES

DECK-O-SHIELD PLUS repels water and protects virtually all porous surfaces, including decks, porches, patios, and walkways around pools. This includes the following surfaces: natural stone, mortar joint, concrete, brick, concrete block, stucco.

Another advantage DECK-O-SHIELD PLUS provides is that the product will not alter the color or tint of the surface after application. There is no need for worry when applying DECK-O-SHIELD PLUS, because the product should have no adverse effects on surface appearance after application.

FEATURES/BENEFITS

- DECK-O-SHIELD PLUS is not a film-forming material - it penetrates the surface to form an integral barrier to moisture penetration.
- Transparent, non-staining.
- High solids content; one-coat application on most surfaces.
- Surface appearance after application and complete drying is virtually unchanged.
- Reduces entrapment of dirt particles and other contaminants that cause discoloration; inhibits soiling.
- Helps protect against efflorescence and rust staining.
- Provides spill and wipe protection from stains.
- Protects against salt staining and "whitening" caused by salt in the water.
- Water-based, VOC compliant.
- One component.

PACKAGING

1 Gallon (3.79 Liter) Units
5 Gallon (18.93 Liter) Pails

COVERAGE

300 - 475 ft.²/gal. (7.36 - 11.66 m²/L). Coverage rate will vary due to the porosity of the substrate.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 40° - 90° F (4° - 32° C), optimum performance and best use is obtained within one year of date of manufacture.

SPECIFICATIONS

- Complies with U.S. EPA, LADCO, and OTC VOC regulations.
- Treated surface is USDA accepted.

TECHNICAL DATA

Dry to Touch: 1 - 2 hours (Typical)
Color: Milky White Emulsion
VOC Content: 254 g/L

APPLICATION

Surface Preparation ... Protect people, vehicles, property, plants, and all non-masonry surfaces from product, splash, residue, and wind drift. Concrete surface must be clean from all stains, oil, grease, dust, dirt, efflorescence, and curing compounds removed prior to application. Though DECK-O-SHIELD PLUS may be applied to slightly damp surfaces, best performance is achieved on a clean, thoroughly dried and absorbent surface. Excessive moisture inhibits penetration, reducing the service life and performance of the treatment. Always test for compatibility.

Surface and Air Temperatures ... Optimum surface and air temperature is 40° - 95° F (4° - 35° C) during application and eight hours after. If freezing conditions exist before application, let surface to receive treatment thaw. The DECK-O-SHIELD PLUS water carrier may freeze at low temperatures or evaporate at high temperatures. Both conditions impair penetration and results.

CONTINUED ON REVERSE SIDE...

deck-o-seal

A DIVISION OF W. R. MEADOWS®

www.deckoseal.com

P.O. BOX 397 • HAMPSHIRE, IL 60140 • PHONE: 800-542-POOL (7665) • FAX: 847-214-2268

Test Application ... Always perform a test application on each type of surface prior to full-scale application to determine suitability and final appearance. Test using the recommended application instructions. Let area dry thoroughly before inspection.

Application Method ... Apply with a low-pressure airless sprayer, such as a Chapin 1949 with a 0.1 GPM (0.379 LPM) spray rate, paint roller or brush, allowing DECK-O-SHIELD PLUS to flood the surface. Roll or brush out puddles. Do not let the product puddle on the surface or dry on the surface. After 10 - 15 minutes, wipe the entire surface with a clean, dry cloth, removing all excess sealer from the surface.

Two coats may be necessary on porous substrates. When applying these two coats, do not allow the first coat to fully dry before applying the second.

Note: Hot, windy conditions will evaporate the water carrier, reducing penetration and performance. On hot, windy days, apply early in the day and in shade, if possible.

Treated surfaces dry to touch in 1 - 2 hours. Protect surfaces from rainfall for six hours following treatment. Many surfaces need several days to develop optimum water repellency.

For denser surfaces, use DECK-O-SHIELD.

Cleanup ... Immediately clean tools, equipment and overspray with soap and warm water.

PRECAUTIONS

DO NOT DILUTE OR ALTER. MIX THOROUGHLY PRIOR TO USE. DO NOT FREEZE. Do not over apply. DECK-O-SHIELD PLUS is a water repellent, not a waterproofing or vapor barrier. DECK-O-SHIELD PLUS should not be applied to surfaces that are to receive caulks or sealants. Application over fully cured elastomeric sealants typically will not affect the sealant. Do not apply to surfaces with temperatures of <40° F (4.4° C) or >95° F (35° C). Prevent from being spilled or over sprayed onto nearby water sources. Temporary darkening of some substrates may occur. Surfaces treated with DECK-O-SHIELD PLUS may prevent adhesion of subsequent coatings. Apply a small test patch application prior to full-scale application. Refer to Safety Data Sheet for complete health and safety information.

LEED INFORMATION

May help contribute to LEED credits:

- IEQ Credit 3.1: Construction Indoor Air Quality Management Plan - During Construction
- IEQ Credit 4.2: Low-Emitting Materials - Paints and Coatings
- MR Credit 5: Regional Materials

For most current data sheet, further LEED information, and SDS, visit www.deckoseal.com.

LIMITED WARRANTY

“DECK-O-SEAL®, A Division of W. R. MEADOWS, INC., warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order.” Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. DECK-O-SEAL cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As DECK-O-SEAL has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.