

POLISHED CONCRETE WITH BELLATRIX MAINTENANCE PROGRAM

- 1. Dry mopping daily with yarn mop or soft micro fiber pad. *Example: wood basketball court mop.*
- 2. Daily, on auto scrubber use micro fiber bonnets over pads.
- 3. Weekly use non aggressive burnishing type pads, White or Cream.
- 4. Monthly medium aggressive burnishing pad, Red, or 1500-3000 grit diamond pad.
- 5. Clean pads, bonnets, or brushes after each use. <u>Very Important!</u>
- 6. Clean up spills in a timely manor.
- 7. Reapply BELLATRIX as needed, check at one year intervals.

Clearners:

Always test your cleaners. Take desired cleaner and mix with water per manufacturer's recommended dilution ratio. Put solution down in a corner or inconspicuous area the size of a half dollar. Let set over night. Use a damp rag to wipe pff any residue. If area is clean with no damage, discoloration, haze, or dullness, product is safe for use on polished concrete. What we want to see after damp wiping is no damaging change in appearance to the polished concrete.

DO **NOT** use cleaning solutions that contain:

- 1. Waxes
- 2. Strippers
- 3. Emulsifiers
- 4. Acidic based materials
- 5. Materials that contain silicates

Use:

- 1. Neutral Cleaners (PH of 7). Check SDS to ensure.
- 2. Example: Ameripolish Shurelock Rejuvenating Cleaner (1-800-592-9320)



Phone:847/214-2100 | Fax:847/683-4544 | www.wrmeadows.com