



W. R. MEADOWS

SEALTIGHT

# Reinforcing Fabric NW<sup>®</sup> Waterproof Reinforcing Fabric

## FEATURES

- Superior Alkali Resistance
- Waterproof
- Lightweight
- Highly Flexible
- Non-toxic
- Non-Allergenic
- Superior Impact Strength
- Economical

## DESCRIPTION

### Basic Use

**Reinforcing Fabric NW** is a non-woven polymeric reinforcing fabric. It is specifically designed to reinforce the **Cem-Kote Flex** materials in applications over dynamic (moving) cracks. It can also be used with **Flex-Top RM** roof and **Tuff-Flex** wall coatings manufactured by Gemite Products Inc.

### Composition and Materials

**Reinforcing Fabric NW** is made of a high quality polymeric fiber with superior durability, resistance to alkali and UV resistance. It contains, integrally embedded, a tough polymer foil, which provides the waterproofing under water head pressure.

### Limitations

One layer of **Reinforcing Fabric NW** alone will provide waterproofing up to 30.6 meters (100 ft.) of water head pressure.

### Health and Safety

**Reinforcing Fabric NW** is non-toxic and non-allergenic. Keep product out of reach of children. FOR INDUSTRIAL USE ONLY. Consult MSDS for additional information.

### Colour

White

### Packaging

**Reinforcing Fabric NW** is available in rolls of 12 cm (4") and 100 cm (40") wide and each roll is 50 m (164 ft.) long.

### Yield

The yield of the roll is 50 linear meters (164 ft.). The actual yield will be lower due to overlaps.

### Storage and Transportation

**Reinforcing Fabric NW**, stored in dry and cool area, has a 1 year shelf life. Protect against sunlight.

## TECHNICAL DATA

Value	Imperial Units	S.I. Units
Construction	Non-Woven	
Breaking Load Long (G.P.20.2-89)	26 lbs/in	69 N/15 cm
Extension at Break Long (G.P.20.2-89)	140%	140%
Breaking Load Lateral (G.P.20.2-89)	17 lbs/in	45 N/15 mm
Extension at Break Lateral (G.P.20.2-89)	480%	480%
Thickness	0.016"	0.42 mm
Colour	White	

## INSTALLATION

Current Guide Specification and Application Instructions contain additional information specific to use of **Reinforcing Fabric NW** in applications of **Flex-Top RM** and **Tuff-Flex** products and must be followed.

## WARRANTY

A limited twelve (12) month Material Replacement Warranty is available. For details contact Technical Service.

## TECHNICAL SERVICE

For technical advice on suitability of **Reinforcing Fabric NW** for specific application, specification assistance and application advise contact Technical Services at 1-800-563-3618.

Continued over ...

**W. R. MEADOWS OF CANADA**  
 70 HANNANT COURT, MILTON, ON L9T 5C1  
 Phone: (905) 878-4122 • Fax: (905) 878-4125  
 Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX  
 Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /  
 St. Albert, AB  
[www.wrmeadows.com](http://www.wrmeadows.com)

*Short Specification*

The reinforcing will be **Reinforcing Fabric NW** manufactured by Gemite® Products Inc., (905-672-2020). It shall be applied in accordance with manufacturer's current guide specifications and application instructions. Contact Technical Service for specification assistance and application instructions.

**MANUFACTURER**

Gemite® Products Inc.,  
1787 Drew Road,  
Mississauga, ON L5S 1J5  
Phone: 905-672-2020 Fax: 905-672-6780  
Website: [www.gemite.com](http://www.gemite.com)

2007-04-11