



Reinforcing Fabric NW® Waterproof Reinforcing Fabric

FEATURES

- Superior Alkali Resistance
- Waterproof
- Lightweight
- Highly Flexible
- Non-toxic
- Non-Allergenic
- Superior Impact Strength
- Economical

DESCRIPTION

Basic Use

Reinforcing Fabric NW is a non-woven polymeric reinforcing fabric. It is specifically designed to reinforce the **Cem-Kote Flex** materials in applications over dynamic (moving) cracks. It can also be used with **Flex-Top RM** roof and **Tuff-Flex** wall coatings manufactured by Gemite Products Inc.

Composition and Materials

Reinforcing Fabric NW is made of a high quality polymeric fiber with superior durability, resistance to alkali and UV resistance. It contains, integrally embedded, a tough polymer foil, which provides the waterproofing under water head pressure.

Limitations

One layer of **Reinforcing Fabric NW** alone will provide waterproofing up to 30.6 meters (100 ft.) of water head pressure.

Health and Safety

Reinforcing Fabric NW is non-toxic and non-allergenic. Keep product out of reach of children. FOR INDUSTRIAL USE ONLY. Consult MSDS for additional information.

Colour

White

Packaging

Reinforcing Fabric NW is available in rolls of 12 cm (4") and 100 cm (40") wide and each roll is 50 m (164 ft.) long.

Yield

The yield of the roll is 50 linear meters (164 ft.). The actual yield will be lower due to overlaps.

Storage and Transportation

Reinforcing Fabric NW, stored in dry and cool area, has a 1 year shelf life. Protect against sunlight.

TECHNICAL DATA

Value	Imperial Units	S.I. Units
Construction	Non-Woven	
Breaking Load Long (G.P.20.2-89)	26 lbs/in	69 N/15 cm
Extension at Break Long (G.P.20.2-89)	140%	140%
Breaking Load Lateral (G.P.20.2-89)	17 lbs/in	45 N/15 mm
Extension at Break Lateral (G.P.20.2-89)	480%	480%
Thickness	0.016"	0.42 mm
Colour	White	

INSTALLATION

Current Guide Specification and Application Instructions contain additional information specific to use of **Reinforcing Fabric NW** in applications of **Flex-Top RM** and **Tuff-Flex** products and must be followed.

WARRANTY

A limited twelve (12) month Material Replacement Warranty is available. For details contact Technical Service.

TECHNICAL SERVICE

For technical advice on suitability of **Reinforcing Fabric NW** for specific application, specification assistance and application advise contact Technical Services at 1-800-563-3618.

Continued over ...

W. R. MEADOWS OF CANADA
70 HANNANT COURT, MILTON, ON L9T 5C1
Phone: (905) 878-4122 • Fax: (905) 878-4125
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
St. Albert, AB
www.wrmeadows.com

Short Specification

The reinforcing will be **Reinforcing Fabric NW** manufactured by Gemite® Products Inc., (905-672-2020). It shall be applied in accordance with manufacturer's current guide specifications and application instructions. Contact Technical Service for specification assistance and application instructions.

MANUFACTURER

Gemite® Products Inc.,
1787 Drew Road,
Mississauga, ON L5S 1J5
Phone: 905-672-2020 Fax: 905-672-6780
Website: www.gemite.com

2007-04-11