



TECHNICAL BULLETIN

CRACK INJECTION USAGE ESTIMATING GUIDE

REZI-WELD™ LV STATE

Approximate Coverage Rates Linear Feet (Linear Meters)					
Crack Width in. (cm)	Crack Depth in. (cm)	Packaging Unit			
		6.1 fl. oz. (180 ml)	16 fl. oz. (475 ml)	3 Gal. (11.34 L)	15 Gal (56.8L)
0.0025 (0.006) [1/400" Crack]	4 (10.2)	75.2 (22.9)	225.6 (68.8)	5,775 (1,760)	28,876 (8,801)
	6 (15.2)	50.1 (15.3)	150.4 (45.8)	3,850 (1,173)	19,250 (5,867)
	8 (20.3)	37.6 (11.5)	112.8 (34.4)	2,887 (880)	14,438 (4,400)
	10 (25.4)	30.1 (9.2)	90.2 (27.5)	2,310 (704)	11,550 (3,520)
	12 (30.5)	25.1 (7.6)	75.1 (22.9)	1,924 (586)	9,621 (2,932)
0.0050 (0.013) [1/200" Crack]	4 (10.2)	37.6 (11.5)	112.8 (34.4)	2,888 (880)	14,438 (4,401)
	6 (15.2)	25.1 (7.6)	75.2 (22.9)	1,925 (587)	9,625 (2,933)
	8 (20.3)	18.8 (5.7)	56.4 (17.2)	1,443 (440)	7,219 (2,200)
	10 (25.4)	15 (4.6)	45.1 (13.8)	1,155 (352)	5,775 (1,760)
	12 (30.5)	12.5 (3.8)	37.6 (11.5)	962 (293)	4,810 (1,466)
0.0156 (0.040) [1/64" Crack]	4 (10.2)	12.1 (3.7)	36.2 (11.0)	925 (282)	4,628(1,410)
	6 (15.2)	8.0 (2.4)	24.1 (7.3)	617 (188)	3,085 (940)
	8 (20.3)	6.0 (1.8)	18.1 (5.5)	462 (141)	2,314 (705)
	10 (25.4)	4.8 (1.5)	14.5 (4.4)	370 (112)	1,851 (564)
	12 (30.5)	4.0 (1.25)	12.1 (3.7)	308 (93)	1,542 (470)
0.0313 (0.079) [1/32" Crack]	4 (10.2)	6.0 (1.8)	18.0 (5.5)	462 (141)	2,310 (704)
	6 (15.2)	4.0 (1.2)	12.0 (3.7)	308 (94)	1,540 (469)
	8 (20.3)	3.0 (0.9)	9.0 (2.8)	231 (70)	1,155 (352)
	10 (25.4)	2.4 (0.7)	7.2 (2.2)	185 (56)	924 (281)
	12 (30.5)	2.0 (0.6)	6.0 (1.8)	154 (47)	770 (234)
0.0625 (0.159) [1/16" Crack]	4 (10.2)	3.0 (0.9)	9.0 (2.8)	231 (71)	1,155 (352)
	6 (15.2)	2.0 (0.6)	6.0 (1.8)	154 (47)	770 (234)
	8 (20.3)	1.5 (0.5)	4.5 (1.4)	116 (35)	578 (176)
	10 (25.4)	1.2 (0.4)	3.6 (1.1)	93 (28)	462 (140)
	12 (30.5)	1.0 (.33)	3.0 (0.9)	77 (23)	385 (116)
0.1250 (0.318) [1/8" Crack]	4 (10.2)	1.5 (0.5)	4.5 (1.4)	116 (35)	578 (176)
	6 (15.2)	1.0 (0.3)	3.0 (0.9)	77 (24)	385 (117)
	8 (20.3)	0.8 (0.2)	2.3 (0.7)	58 (18)	289 (88)
	10 (25.4)	0.6 (0.2)	1.8 (0.6)	46 (14)	231 (70)
	12 (30.5)	0.5 (0.17)	1.5 (0.5)	38 (12)	192 (58)



W. R. MEADOWS, INC. | P.O. Box 338 | HAMPSHIRE, IL 60140-0338
 Phone: 847/214-2100 | Fax: 847/683-4544 | www.wrmeadows.com



TECHNICAL BULLETIN

CRACK INJECTION USAGE ESTIMATING GUIDE

REZI-WELD LV STATE

Values are approximate and will vary depending on waste, concrete and user technique.

Capping cracks using REZI-WELD GEL PASTE STATE in a 8.6 oz. (254 ml) cartridge will cap approximately 7 linear feet (2.1 linear meters) of a crack with a 3/16 in. (4.7 mm) thick by 1 in. (25.4 mm) wide bead.

Capping cracks using REZI-WELD GEL PASTE STATE in a 21.2 oz. (627 ml) cartridge will cap approximately 16 linear feet (4.8 linear meters) of a crack with a 3/16 in. (4.7 mm) thick by 1 in. (25.4 mm) wide bead.

