



TECHNICAL BULLETIN

VOCOMP INTERIOR APPLICATION MAINTENANCE

The following steps are recommended for proper cleaning and maintenance of concrete previously treated with VOCOMP series product in interior applications:

- Routine dust mopping, sweeping, vacuuming. This will help remove any dust, dirt, grit, etc.; which can dull the appearance of the sealer, if left on the surface.
- Routine damp-mopping with a mild, commercially available cleaner*. Avoid cleaners that contain ammonia, harsh chemicals, abrasives, etc.
- Periodic application of a commercially available concrete floor wax*.
- Wipe up liquid spills as quickly as possible. Do not allow water or other liquids to puddle and remain on the surface of the sealed concrete.

*Follow all manufacturer recommended use, application, safety and handling instructions.

Note: While VOCOMP series products help protect concrete from stain absorption, these products are not 100% stain resistant. Removing the substance as quickly as possible from the sealed surface helps prevent the stain from reaching the concrete.

The frequency of cleaning and maintenance, as well as the frequency of concrete resealing is dependent on the amount of foot traffic, type of contaminant(s), frequency of exposure to contaminant(s), liquids, etc.

Products in the VOCOMP line are VOCOMP-20, VOCOMP-25, and VOCOMP-30.



W. R. MEADOWS, INC. | P.O. Box 338 | HAMPSHIRE, IL 60140-0338
Phone: 847/214-2100 | Fax: 847/683-4544 | www.wrmeadows.com