



DATA SHEET NO. 2900-1100

1100 RUBBERIZED CRACK FILLER

DESCRIPTION

1100 RUBBERIZED CRACK FILLER is an emulsified asphalt containing rubber and selected fillers designed for sealing cracks in asphalt and concrete pavements. It is cold applied.

USES

1100 RUBBERIZED CRACK FILLER is designed for sealing cracks in asphalt and concrete pavements.

FEATURES/BENEFITS

- Cold-applied/Ease of application
- Seals cracks in both asphalt and concrete

PACKAGING

18.9 L (5 U.S. Gal.) Pails 205 L (54.2 U.S. Gal.) Drums 1000 L (265 U.S. Gal.) Totes* Also available in bulk *Lightweight Disposable Tote System

COVERAGE

7 m/L (87 ft./gal.)

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

STANDARDS/SPECIFICATIONS

 Complies with Alberta Transportation Specification EC-101

TECHNICAL DATA

I EOIIIIIOAE DAIA	
Colour	Brown; Black when cured
Solids Content	Approximately 65%
	Skins in 15 minutes at average
	spring temperature
Viscosity @ 25° C	70 - 90 Krebs
Uniformity	Smooth in consistency; no settlement
24 Hour Rate of Curing	55 - 60%

APPLICATION

Surface Preparation ... Clean cracks and joints and remove all loose material using compressed air. Fill deep cracks to within 51 mm (2") of pavement with clean sand.

W. R. MEADOWS® OF CANADA

70 Hannant Court, Milton, ON L9T 5C1 38 Rayborn Crescent, St. Albert, AB T8N 4B1 (800) 342-5976

Montreal Sales: (877) 405-5186

Application Method ... Apply with gravity-feed type pour pots or diaphragm pump system. Sprinkle sand or cement powder on uncured material to prevent tracking. Some cracks may require refilling after the application has cured. Minimum application temperature is 10° C.

Clean-Up ... Use water to clean up fresh material. Dried material may be cleaned up with mineral spirits.

PRECAUTIONS

DO NOT FREEZE. Minimum application temperature is 10° C. Do not use if there is a possibility of rain. Refer to Safety Data Sheet for complete Health and Safety information.

MASTERFORMAT NUMBER AND TITLE

32 01 17.61 - Sealing Cracks in Asphalt Paving

LEED INFORMATION

May help contribute to LEED credits:

 MRc9: Construction and Demolition Waste Management

For most current data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

2020-01-20



Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON St. Albert, AB

www.wrmeadows.com