



## A-500 OIL SPOT PRIMER

DATA SHEET NO. 2900-A500

### DESCRIPTION

A-500 OIL SPOT PRIMER is a quick drying latex emulsion formulated to provide a protective barrier over oil, grease, gasoline, or chemical spills prior to application of sealer.

### USES

A-500 OIL SPOT PRIMER can be used on any asphalt surface, including parking lots, driveways, airport runways and aprons, traffic safety islands, and golf cart paths.

### PACKAGING

18.9 L (5 U.S. gallon) pails

### COVERAGE

Coverage is approximately 4.8 m<sup>2</sup>/L (200 ft.<sup>2</sup>/gal).

### PHYSICAL PROPERTIES

Color when dry Clear

### PRECAUTIONS

Stir before using. Do not freeze. Do not store in direct sunlight. Do not store containerized sealer above 38° C (100° F). Containers should be closed when not in use.

Refer to Material Safety Data Sheet for complete health and safety information.

### APPLICATION

**Surface Preparation** ... Scrape off and remove excess build up of oil, grease, or other chemicals before application.

**Application Method** ... Mix well before using. Dilute with water 2 to 1. On heavy oil spills, mix 1 to 1. Allow to completely cure before sealing. Do not apply when temperatures are below 10° C (50° F) or if rain is evident or forecast.

### CLEANUP

While still wet, clean tools and equipment with soap and water. Use solvent if material has dried.

**TO VERIFY MOST RECENT TECHNICAL DATA SHEET IS BEING USED, VISIT OUR WEBSITE:**

[www.wrmeadows.com](http://www.wrmeadows.com)

2009-02-28



**W. R. MEADOWS OF WESTERN CANADA**  
38 Rayborn Crescent, St. Albert, AB T8N 5B4  
Phone: (780) 458-8773 • Fax: (780) 458-1173

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX  
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /  
St. Albert, AB

[www.wrmeadows.com](http://www.wrmeadows.com)