



## SPECTRUM SURFACE ENHANCER

Adhesion Promoter

DATA SHEET NO. 3300-950

### DESCRIPTION

SPECTRUM SURFACE ENHANCER is a water-based product, specifically formulated to be used as an additive for SPECTRUM WATER-BASED STAIN from W. R. MEADOWS. Adding SPECTRUM SURFACE ENHANCER provides optimum adhesion to the concrete and will improve the ultimate durability of the stain. SPECTRUM SURFACE ENHANCER is non-flammable, non-combustible, non-hazardous, eco-friendly, and VOC-compliant. SPECTRUM SURFACE ENHANCER may also be used as a prime coat prior to the application of SPECTRUM WATER-BASED STAIN.

### USES

SPECTRUM SURFACE ENHANCER is specifically formulated to be used as an additive for SPECTRUM WATER-BASED STAIN

### PACKAGING

3.79 litre (1 U.S. Gallon) containers  
18.93 litre (5 U.S. Gallon) pails

### LEED INFORMATION

May help contribute to LEED credits:

- MR Credit 5.1: Regional Materials: 10% Extracted, Processed & Manufactured Regionally
- MR Credit 5.2: Regional Materials: 20% Extracted, Processed & Manufactured Regionally
- EQ Credit 4.2: Low Emitting Materials – Paints and Coatings

### FEATURES AND BENEFITS

- Improves adhesion and durability of SPECTRUM WATER-BASED STAIN.
- User friendly
- Non-flammable, non-combustible
- Low odour
- Easy water cleanup
- VOC compliant

### TECHNICAL DATA (Typical)

Appearance:	Clear Liquid
Solids, Wt. %:	10 +/- 2
Weight per 3.79 L (1 U.S. gal.):	4.5 kg (8.9 lb.)
VOC, g/L	0
FLASH POINT	>100°C (>212°F)

### COVERAGE\*

Approximately 6.1 m<sup>2</sup>/L (250 ft.<sup>2</sup>/gal.), when used as a primer and approximately 12.3 m<sup>2</sup>/L (500 ft.<sup>2</sup>/gal.), when used as an additive with the SPECTRUM WATER-BASED STAINS, Natural Series (Solid) Colours. The recommended dilution ratio for base colours applied to concrete is 1 part colour concentrate to 2 parts Surface Enhancer to 2 parts de-ionized or reverse osmosis water.

\*Coverage will vary due to dilution ratio (of the stain), profile, porosity, application technique, condition of the substrate, etc.

### REGULATORY COMPLIANCE - VOC

SPECTRUM SURFACE ENHANCER meets all applicable federal, state, district and local AIM VOC regulations.

### PRECAUTIONS/LIMITATIONS

- Do not use on previously stained floors (designed for use in first coat of stain)
- Do not use SPECTRUM SURFACE ENHANCER on cementitious overlays, micro-toppings, etc.
- Do not use as a primer if the surface contains a sealer, paint, concrete curing compound coating, adhesive, etc., or was previously treated with a penetrating product such as a silicate, silane, siloxane, etc.

Continued over ...

**W. R. MEADOWS OF CANADA**  
70 Hannant Court, Milton, ON L9T 5C1  
Phone: (905) 878-4122 • Fax: (905) 878-4125  
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX  
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /  
St. Albert, AB  
[www.wrmeadows.com](http://www.wrmeadows.com)

### **SHELF LIFE (TYPICAL)**

One year in unopened, factory-sealed container. Store in a dry area, away from moisture, at 4 - 32° C (40 - 90° F).

### **SURFACE PREPARATION AND APPLICATION**

For detailed surface preparation and application instructions, please refer to the W. R. MEADOWS guide DETAILED APPLICATION INSTRUCTIONS FOR SPECTRUM WATER-BASED STAIN.

**Primer:** When used as primer for a SPECTRUM WATER-BASED STAIN, apply SPECTRUM SURFACE ENHANCER directly to the concrete surface, using a roller, at approximately 6.1 m<sup>2</sup>/L (250 ft.<sup>2</sup>/gal.). Allow SPECTRUM SURFACE ENHANCER to dry to touch prior to application of SPECTRUM WATER-BASED STAIN.

**Additive:** Refer to the W. R. MEADOWS guide DETAILED APPLICATION INSTRUCTIONS FOR SPECTRUM WATER-BASED STAIN.

### **HEALTH AND SAFETY**

If contact with the skin or eyes occurs, flush area with water. Consult product Material Safety Data Sheet (MSDS) for complete health and safety information prior to using.

**FOR THE MOST CURRENT PRODUCT INFORMATION ... VISIT OUR WEBSITE AT [www.wrmeadows.com](http://www.wrmeadows.com).**

2009-05-26



© SEALTIGHT is a registered trade mark of W. R. Meadows

**WARRANTY:** W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.