



520 SEALMASTIC™ Damproofing Emulsion

DESCRIPTION

520 SEALMASTIC emulsion is a mineral colloid emulsion for use as a dampproof coating.

USES

520 SEALMASTIC emulsion is ideal for reducing dampness and moisture infiltration through foundation walls, parapets, firewalls, tanks, culverts, cisterns, and bridge abutments. The product is also applicable for below-grade masonry wall dampproofing. 520 SEALMASTIC is compatible with ICF foam forms

FEATURES/BENEFITS

- Can be used on a variety of substrates.
- Provides excellent dampproofing properties.
- Compatible with Styrofoam.

PACKAGING

18.9 Litre Pails

COVERAGE

Coverage is 0.39 - 0.74 m²/L (16 - 30 ft.²/gal.) depending on porosity of the surface.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

SPECIFICATIONS/STANDARDS

Complies with CAN/CGSB-37.2-M88. To be applied according to CAN/CGSB-37.3-M89.

TECHNICAL DATA

| Black |
|----------------------|
| 54% |
| 1 kg/L (10 lb./gal.) |
| 2° C Minimum |
| |
| Non-Combustible |
| Burns |
| 95° C |
| |

APPLICATION

Surface Preparation ... Surface shall be firm and free from loose particles, cracks, grease, oil, frost, snow, ice, and other foreign matter. Surface may be damp, but not wet. Prime with 50% diluted 520 SEALMASTIC. Dilute with clean water only.

Mixing ... Mix thoroughly before application.

W. R. MEADOWS® OF CANADA 70 Hannant Court, Milton, ON L9T 5C1

21 Streambank Ave., Sherwood Park, AB T8H 1N1 (800) 342-5976

Montreal Sales: (514) 865-2406

DATA SHEET NO. 7110-520

Application Method ... Apply by brush, trowel, glove or sprayer. Protect uncured emulsion from precipitation. Protect walls with PROTECTION COURSE (VIBRAFLEX® PC) from W. R. MEADOWS during backfill operations.

Drying Time ... Touch dry: 2 hours. Firm dry: 24 hours.

Cleanup ... Use water for cleanup of uncured emulsion. Use mineral spirits for cleanup of cured emulsion.

PRECAUTIONS

520 SEALMASTIC is a water/asphalt emulsion and will freeze. **Do not allow to freeze.**

MASTERFORMAT NUMBER AND TITLE

07 11 13 - Bituminous Dampproofing

For most recent data sheet, LEED information, and SDS, visit www.wrmeadows.com.

2022-11-01



Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON Sherwood Park, AB www.wrmeadows.com info@wrmeadows.com

| ® SEALTIGHT is a registered trademark of W. R. Meadows WARRANTY: W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials w published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSINEXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHE this Warranty, we will replace defective materials, provided however, that the buyer examine the materials when received and the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential dam: warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in a or application of the performance of materials under any particular condition. Neither this Warranty nor our liability may be extern representatives, or by our distributor's representatives, or by any sales information or drawings. | /E AND IN LIEU OF ANY OTHER WARRANTY, PARTICULAR PURPOSE AND ALL OTHER KRWISE. As the exclusive remedy for breach of promptly notify us in writing of any defect before the materials, all our Warranty and other duties terminates and no action for breach of any such ages. Unless otherwise agreed to in writing, no any way guarantee any particular method of use |
|--|---|