



610 All Weather Fibrated Roof Coating

DESCRIPTION

610 All Weather Fibrated Roof Coating is a solvent cutback type roof coating that provides a tough flexible waterproof coating.

USE

610 All Weather Fibrated Roof Coating is designed for use as a re-roofing material over existing built-up roofs and other roof surfaces to prolong their life. It can be applied over asphalt, wood, asbestos, gypsum and steel.

LIMITATIONS

Avoid use where solvent odors are objectionable.

PACKAGING

18.9 Litre Pails

Standards

Complies with CAN/CGSB-37.8-M88. To be applied according to CGSB 37-GP-14M.

Working Characteristics

Coverage from 100 ft²/gal (2.1 m²/L) to 150 ft²/gal (3.1 m²/L) depending on porosity of the surface. If the material has thickened due to low temperatures leave the container in a heated building overnight. **DO NOT HEAT WITH AN OPEN FLAME.**

DATA SHEET NO. 7500-610

PHYSICAL PROPERTIES

Color	Black
Solids	61%
Weight	10 lbs/gal (1 kg/L)
Drying Time	
Touch dry	3.5 hours
Firm dry	24 hours
Application Temperature	4°F (-20°C) Minimum
Flammability	
Wet	Flammable
Dry	Burns
Moisture Permeance	.05 Perms at 1/8" film
Water Content	1% maximum
Flash Point	104°F (43°C)

APPLICATION

Preparatory Work

Surface shall be firm and free from loose particles, cracks, grease, oil, frost, snow, ice, and other foreign matter. Surface must be free from frost, snow and ice. Patch problem areas with #625 Plastic Cement

Installation Instructions

- Mix thoroughly.
- At temperatures below 40°F (4°C) use a prime coat of 600 Asphalt Primer.
- Apply by brush or sprayer at a minimum rate of 150 ft²/gal (3.1 m²/L).
- If necessary, apply a second coat.

Safety Precautions

Contains flammable solvents. Use in a well-ventilated area. **KEEP AWAY FROM HEAT AND OPEN FLAMES.**

W. R. MEADOWS OF WESTERN CANADA
38 Rayborn Crescent, St. Albert, AB T8N 5B4
Phone: (780) 458-8773 • Fax: (780) 458-1173

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
St. Albert, AB
www.wrmeadows.com



2005-01-07

© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.