



DATA SHEET NO. 7500-625

625 PLASTIC CEMENT All-Purpose Asphalt Mastic

DESCRIPTION

625 PLASTIC CEMENT is a solvent cutback, fibrated, asphalt mastic that forms a tough, flexible, water-resistant coating.

USES

625 PLASTIC CEMENT is designed as a general utility cement for filling and sealing joints in concrete, masonry, wood, or metal building construction; or for sealing flashings, skylights, and parapet walls; and for repairing leaks and cracks of all types.

FEATURES/BENEFITS

- Forms a tough, flexible coating.
- Water-resistant.
- Can be used in a variety of applications.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

PACKAGING

4 Kg. Pails
10 Kg. Pails
20 Kg. Pails

COVERAGE

Coverage will vary depending on usage.

SPECIFICATIONS

Complies with CAN/CGSB-37.5-M89. To be applied according to CGSB 37-GP-11M.

TECHNICAL DATA

Colour	Black
Solids	75%
Weight	1.15 kg/L (11.5 lb./gal.)
Drying Time	8 hours average
Touch dry	3 hours
Firm dry	24 hours
Application temperature	-20° C minimum
Flammability	
Wet	Flammable
Dry	Burns
Water Content	1% Maximum

APPLICATION

Surface Preparation ... Surface shall be firm and free from loose particles, cracks, grease, oil, and other foreign matter. Surface must be free from frost, snow, and ice.

Application Method ... Apply by knife, trowel, or glove. Single coatings should not be more than 6 mm (1/4") thick.

Cleanup ... Use mineral spirits for cleanup.

PRECAUTIONS

Contains flammable solvents. **KEEP AWAY FROM HEAT AND OPEN FLAME.** Use in a well-ventilated area. Avoid use where solvent odours are objectionable. If material has thickened due to low temperatures, leave the containers in a heated building overnight. **DO NOT HEAT WITH AN OPEN FLAME.**

MASTERFORMAT NUMBER AND TITLE

07 00 00 - Thermal and Moisture Protection

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management

2017-10-20

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
38 Rayborn Crescent, St. Albert, AB T8N 4B1
(800) 342-5976
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
St. Albert, AB
www.wrmeadows.com

© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.