



DATA SHEET NO. 7500-630

630 LAP CEMENT

DESCRIPTION

630 LAP CEMENT is a solvent cutback, fibrated, asphalt mastic used in the application of asphalt roofing products.

USES

630 LAP CEMENT is designed to be used with rolled asphalt felts, mineral surfaced roofing, or asphalt shingles to bond the laps or edges of the felt or shingle.

PACKAGING

3.78 L Pails
18.9 L Pails

COVERAGE

Coverage will be between 2.1 m²/L (100 ft²/gal.) and 3.1 m²/L (150 ft.²/gal.)

SPECIFICATIONS

- CAN/CGSB-37.4-M89 (applied according to CGSB 37-GP-10M)

TECHNICAL DATA

Table with 2 columns: Property and Value. Includes Color (Black), Solids (65%), Weight (1.1 kg/L), Drying Time (8 hours average), Application Temperature (-20° C min.), Flammability (Flammable), Water Content (1% Maximum), and Flash Point (40° C).

APPLICATION

Surface Preparation ... The lap joints should be clean, dry, free from oil, grease, frost, snow, ice, and other foreign matter.

Application Method ... Apply by knife, trowel, brush, or roofer's mop.

Cleanup ... Use mineral spirits for cleanup.

PRECAUTIONS

630 LAP CEMENT will not bond to greasy surfaces. Do not use more material than needed, as blistering may result in hot weather. If material has thickened due to low temperatures, leave the containers in a heated building overnight. DO NOT HEAT WITH AN OPEN FLAME.

HEALTH AND SAFETY

Use in a well ventilated area. Contains flammable solvents. KEEP AWAY FROM HEAT AND OPEN FLAME.

2004 MASTERFORMAT NUMBER AND TITLE

07 72 00 – Roof Accessories

LEED INFORMATION

- May help contribute to LEED credits:
- IEQ Credit 4.2: Low Emitting Materials – Paints and Coatings
- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

For most recent data sheet, further LEED information, and MSDS, visit www.wrmeadows.com.



2010-10-29

W. R. MEADOWS OF WESTERN CANADA
38 Rayborn Crescent, St. Albert, AB T8N 5B4
Phone: (780) 458-8773 • Fax: (780) 458-1173

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON /
St. Albert, AB
www.wrmeadows.com

© SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Western Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Western Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Western Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Western Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.